

# UNIX Automotive SAE 15W-40 multigrade motor oil

## Product benefits

- ideal for older vehicles
- reduces oil consumption

## Applications

UNIX Automotive SAE 15W-40 motor oil is recommended to use in WE and Japanese cars with engines designed before 1989, and in four-stroke gasoline engines manufactured in EE, or wherever the specifications in the manual call for the listed or lower performance levels.

Unless otherwise instructed in the car operating manual the recommended drain interval is maximum 10.000 km, or one year.

## Specifications and approvals

API SF/CC

## Product description

UNIX Automotive SAE 15W-40 motor oil is manufactured from highly refined premium mineral base oils with complex additive system (detergent, dispersant, antioxidant, antiwear, anticorrosive and antifoam agents, pour point depressant, and viscosity modifier).

## Typical properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,885
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	105,8
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	14,1
Viscosity index	135
Pour point [°C]	-27
Flash point (Cleveland) [°C]	225

The characteristics in table are typical values of the product and do not constitute a specification.

## Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Shelf life in the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C