UNIX Automotive SAE 10W-40 semi-synthetic motor oil

Product benefits

- high performance, long engine life
- stay-in-grade shear stability and excellent wear protection
- applicable in common-rail diesel engines
- optimal viscosity at high temperature
- low volatility and low oil consumption

Applications

UNIX Automotive SAE 10W-40 is an ideal lubricant for naturally aspirated or turbocharged engines of gasoline and diesel passenger cars and light commercial vehicles.

Thanks to its special base oil and additive composition, Unix X4 10W-40 engine oil can fulfil the requirements of long drain intervals, under severe conditions, in vehicles which require the listed performance levels.

Specifications and approvals

ACEA A3/B3-08 API SL/CF

Product description

UNIX Automotive SAE 10W-40 motor oil is manufactured from high performance synthetic and highly refined premium mineral base oils with complex additive system (detergent, dispersant, antioxidant, antiwear, anticorrosive and antifoam agents, pour point depressant, and viscosity modifier).

Typical properties

| Properties | Typical values |
|---------------------------------------|----------------|
| Density at 15°C [g/cm3] | 0,870 |
| Kinematic viscosity at 40°C [mm2/s] | 93,6 |
| Kinematic viscosity at 100 °C [mm2/s] | 13,8 |
| Viscosity index | 150 |
| Pour point [°C] | -33 |
| Flash point (Cleveland) [°C] | 225 |
| Base number (BN) [mg KOH/g] | 8 |

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Shelf life in the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Latest revision: 2018.02.01 12:22 Version 003.000.