

Product Data Sheet

Revised: 2018/10/16 (version 3.5)



PETRONAS

PETRONAS Tutela Multi MTF 700 75W-80

Designed to be the Fluid Technology Solution of choice providing excellent protection and longer oil life for manual transmissions

Description and Applications

PETRONAS Tutela Multi MTF 700 is a premium fully synthetic multi-vehicle Manual Transmission Fluid delivering optimized synchronizer performances and component durability for today's manual transmissions over their standard service life. Its wide coverage of major manufacturer specifications, extensive bench testing and field-testing, makes it suitable for use in virtually all manual transmissions requiring API GL4. For this reason, Tutela Multi MTF 700 reduces the risk of using the wrong oil and simplifies inventory management.

Benefits

PETRONAS Tutela Multi MTF 700 enhances your vehicle availability while significantly reducing your operating costs through:

- **Fuel Economy** performance by **optimized transmission efficiency:**
 - o A lower viscosity fluid to help reduce operational energy losses.
- **Extended Transmission Life** driven by:
 - o Exceptional thermal and oxidation stability under high temperature, providing viscosity stability and preventing formation of deposits and sludge to prolong oil life
 - o Enhanced shear stability for a constant film strength and effective lubrication to protect all moving parts
 - o Excellent anti-wear, gear and bearing protection to extend components life
 - o Extended transmission fluid life and prevention against fluid breakdown at higher operating temperatures for a total protection of the transmission
 - o Seal compatibility for better leakage prevention
 - o Robust corrosion protection on yellow metals and steel
 - o Broad synchronizer materials compatibility

Provides outstanding Driving Experience through:

- **Outstanding synchronizer performance** at a wide temperature range for a comfortable shifting
- **Exceptional low temperature viscosity** for improved lubrication during start-up and shifting comfort in cold conditions

Approvals, Specifications and Recommendations

PETRONAS Tutela Multi MTF 700 is a fully synthetic lubricant that meets and exceeds below performances:

Approvals and Specifications:

- API GL-4

Meets or Exceeds the performance requirements of:

- AUDI / SEAT / SKODA / VW G 052 317, G 052 171, G 052 178, G 052 512, G 052 726, G 060 726, G 50, GO 52 527, GO 70 726
- BMW MTF LT-2, LT-3, LT-4
- FORD WSD-M2C200-C; FORD WSS-M2C200-D2
- GM 194004 / 19259104; GM 1940182 / 1940764 / 1940768
- NISSAN MT-XZ, MT-XZ TL (JR Type)
- PSA B712330
- LAND ROVER SPECIAL GEAR OILMTF 94
- HONDA MTF, MTF-II, MTF-III
- RENAULT MTF type NFJ, NFP, TRJ, TRT, TRZ
- VOLVO 97308, 97309

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.860
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	9.3
Viscosity Index	ASTM D 2270	-	155
Brookfield Viscosity @-40°C	ASTM D 2983	mPa.s (cP)	54000
Pour Point	ASTM D 97	°C	-45
Flash Point COC	ASTM D 92	°C	230

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The data sheet and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 1628