

A.Z. Meisterteile Motorenöl MT-8F 0W-30 synthetic motor oil

Product benefits

- fuel saving operation
- excellent cold pumping properties
- outstanding wear protection
- premium quality raw materials

Applications

A.Z. Meisterteile Motorenöl MT-8F 0W-30 is a premium performance, fuel saving synthetic engine oil produced using dual lubricating film technology from synthetic base oils and a complex additive system, ensuring excellent flow characteristics, for use in the most advanced automobile engines. Its advantages can be fully exploited by using it in the latest engines manufactured with narrow clearances. For certain engine types, ACEA (the European Association of Vehicle Manufacturers) does not recommend engine oils with C2 performance, because of their specially low viscosity. Please refer to the relevant recommendations by the engine manufacturers!

Specifications and approvals

ACEA C2
Ford WSS-M2C-950-A
Jaguar Land Rover STJLR.03.5007

Product description

The A.Z. Meisterteile Motorenöl MT-8F 0W-30 is a top tier engine oil, manufactured from synthetic base oils and complex additive system (detergent/dispersant, antioxidant, antiwear, anticorrosive and antifoam agents, flow improver) provide excellent cold flow characteristics and offers the highest performance levels for passenger cars.

It provides perfect engine protection and protects from intensive wear typically occurring at cold-starts under extreme cold conditions as well. Enables trouble-free cold-start and protects battery.

Due to its low evaporation characteristics the product reduces oil consumption, and consequently exhaust emission of harmful chemicals. Its excellent oxidation stability specific to synthetic oils ensures the original properties to remain unchanged even at permanently high engine operating temperatures.

Typical properties

Properties	Typical values
Appearance	brown, bright, clear
Density at 15°C [g/cm ³]	0,847
Kinematic viscosity at 40 °C [mm ² /s]	49,4
Kinematic viscosity at 100 °C [mm ² /s]	9,7
Pour point [°C]	-45
Flash point (Cleveland) [°C]	254

The characteristics in table are typical values of the product and do not constitute a specification.

A.Z. Meisterteile Motorenöl MT-8F 0W-30
synthetic motor oil

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

Shelf life in the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C