



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 23

TEROSON SB S3000 WH BO1L EGFD

SDS No. : 684051
V004.0

Revision: 27.06.2022

printing date: 19.08.2022

Replaces version from: 24.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON SB S3000 WH BO1L EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Underbody coating

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements**Label elements (CLP):****Hazard pictogram:****Contains**

Xylene - mixture of isomeres

Signal word:

Warning

Hazard statement:

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Supplemental information

Contains: Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine;
 Hexanoic acid, 2-ethyl-, cobalt(2+) salt May produce an allergic reaction.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P260 Do not breathe vapours.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**

P370+P378 In case of fire: Use CO₂, dry chemical, or foam for extinction.

**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Xylene - mixture of isomeres 1330-20-7 215-535-7 01-2119488216-32	20- 40 %	Asp. Tox. 1, H304 Acute Tox. 4, Inhalation, H332 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412		EU OEL
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9 927-241-2 01-2119471843-32	5- < 10 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412		
ethylbenzene 100-41-4 202-849-4 01-2119489370-35	5- < 10 %	Flam. Liq. 2, H225 Acute Tox. 4, Inhalation, H332 Asp. Tox. 1, H304 STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336		EU OEL
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	0,25- < 2,5 %	Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Toluene 108-88-3 203-625-9 01-2119471310-51	0,1- < 1 %	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, Inhalation, H373 Skin Irrit. 2, H315 STOT SE 3, Inhalation, H336 Aquatic Chronic 3, H412		EU OEL
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7 205-250-6 01-2119524678-29	0,01- < 0,1 %	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412 Eye Irrit. 2, H319 Repr. 1B, H360 Carc. 1B, H350	M acute = 1	

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Storage at 5 to 25°C is recommended.

7.3. Specific end use(s)

Underbody coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	50	220	Time Weighted Average (TWA):		EH40 WEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	100	441	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	441	Time Weighted Average (TWA):		EH40 WEL
Ethylbenzene	100	442	Time Weighted Average	Indicative	ECTLV

100-41-4 [ETHYLBENZENE]			(TWA):		
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	125	552	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		EH40 WEL
Talc (Mg3H2(SiO3)4) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [Silica, amorphous, inhalable dust]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [Silica, amorphous, respirable dust]		2,4	Time Weighted Average (TWA):		EH40 WEL
Toluene 108-88-3 [TOLUENE]	50	191	Time Weighted Average (TWA):		EH40 WEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Cobalt bis(2-ethylhexanoate) 136-52-7 [COBALT AND COBALT COMPOUNDS (AS CO)]		0,1	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	50	221	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECLTV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	100	442	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Calcium carbonate 471-34-1 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative	ECTLV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Kaolin 1332-58-7 [KAOLIN]		2	Time Weighted Average (TWA):		IR_OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC]		0,8	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECTLV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Xylene - mixture of isomeres 1330-20-7	aqua (freshwater)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (freshwater)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	Soil				2,31 mg/kg		
Xylene - mixture of isomeres 1330-20-7	aqua (marine water)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	aqua (intermittent releases)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sewage treatment plant (STP)		6,58 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (marine water)				12,46 mg/kg		
ethylbenzene 100-41-4	aqua (intermittent releases)		0,1 mg/l				
ethylbenzene 100-41-4	aqua (freshwater)		0,1 mg/l				
ethylbenzene 100-41-4	sediment (marine water)				1,37 mg/kg		
ethylbenzene 100-41-4	sediment (freshwater)				13,7 mg/kg		
ethylbenzene 100-41-4	sewage treatment plant (STP)		9,6 mg/l				
ethylbenzene 100-41-4	aqua (marine water)		0,01 mg/l				
ethylbenzene 100-41-4	Soil				2,68 mg/kg		
ethylbenzene 100-41-4	oral				20 mg/kg		
Toluene 108-88-3	aqua (freshwater)		0,68 mg/l				
Toluene 108-88-3	sediment (freshwater)				16,39 mg/kg		
Toluene 108-88-3	sediment (marine water)				16,39 mg/kg		
Toluene 108-88-3	Soil				2,89 mg/kg		
Toluene 108-88-3	sewage treatment plant (STP)		13,61 mg/l				
Toluene 108-88-3	aqua (marine water)		0,68 mg/l				
Toluene 108-88-3	aqua (intermittent releases)		0,68 mg/l				
Cobalt bis(2-ethylhexanoate) 136-52-7	aqua (freshwater)		0,0006 mg/l				
Cobalt bis(2-ethylhexanoate) 136-52-7	aqua (marine water)		2,36 µg/l				
Cobalt bis(2-ethylhexanoate) 136-52-7	sediment (freshwater)				9,5 mg/kg		
Cobalt bis(2-ethylhexanoate) 136-52-7	sediment (marine water)				9,5 mg/kg		
Cobalt bis(2-ethylhexanoate) 136-52-7	Soil				10,9 mg/kg		
Cobalt bis(2-ethylhexanoate) 136-52-7	sewage treatment plant (STP)		0,37 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - systemic effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - local effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - local effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - local effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	Workers	inhalation	Long term exposure - systemic effects		871 mg/m3	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	Workers	dermal	Long term exposure - systemic effects		77 mg/kg	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	General population	inhalation	Long term exposure - systemic effects		185 mg/m3	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	General population	dermal	Long term exposure - systemic effects		46 mg/kg	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	General population	oral	Long term exposure - systemic effects		46 mg/kg	
ethylbenzene 100-41-4	Workers	inhalation	Acute/short term exposure - local effects		293 mg/m3	
ethylbenzene 100-41-4	General population	inhalation	Long term exposure - systemic effects		15 mg/m3	
ethylbenzene 100-41-4	General population	oral	Long term exposure - systemic effects		1,6 mg/kg	
ethylbenzene 100-41-4	Workers	dermal	Long term exposure - systemic effects		180 mg/kg	
ethylbenzene 100-41-4	Workers	inhalation	Long term exposure - systemic effects		77 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - local effects		384 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - systemic effects		384 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Long term exposure - local		192 mg/m3	

			effects			
Toluene 108-88-3	Workers	Inhalation	Long term exposure - systemic effects		192 mg/m3	
Toluene 108-88-3	Workers	dermal	Long term exposure - systemic effects		384 mg/kg	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - local effects		226 mg/m3	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - systemic effects		226 mg/m3	
Toluene 108-88-3	General population	Inhalation	Long term exposure - systemic effects		56,5 mg/m3	
Toluene 108-88-3	General population	dermal	Long term exposure - systemic effects		226 mg/kg	
Toluene 108-88-3	General population	oral	Long term exposure - systemic effects		8,13 mg/kg	
Toluene 108-88-3	General population	inhalation	Long term exposure - local effects		56,5 mg/m3	
Cobalt bis(2-ethylhexanoate) 136-52-7	Workers	Inhalation	Long term exposure - local effects		0,2351 mg/m3	
Cobalt bis(2-ethylhexanoate) 136-52-7	General population	Inhalation	Long term exposure - local effects		0,037 mg/m3	
Cobalt bis(2-ethylhexanoate) 136-52-7	General population	oral	Long term exposure - systemic effects		55,8 µg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Xylene 1330-20-7 [XYLENE O-, M-, P-, OR MIXED ISOMERS]	Methylhippuric acids	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:
Use only in well ventilated areas.

Respiratory protection:
In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).
This recommendation should be matched to local conditions.

Hand protection:
Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; \geq 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; \geq 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	liquid
Colour	White
Odor	aromatic
Melting point	Currently under determination
Initial boiling point	126 - 149 °C (258.8 - 300.2 °F)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	26,5 °C (79.7 °F); Flash Point in closed cup
Auto-ignition temperature	Currently under determination
Decomposition temperature	Currently under determination
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	210 - 336 mm ² /s ;no method
Viscosity, dynamic	250 - 400 mPa.s Viscosity Physica; HT-Method
()	
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	37 mbar
Density	1,19 - 1,23 g/cm ³ Dichte Pyknometer; HT-Methode; Henkel
(20 °C (68 °F))	Iberica NS-06
Relative vapour density:	Currently under determination
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidizers.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
ethylbenzene 100-41-4	LD50	3.500 mg/kg	rat	not specified
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Toluene 108-88-3	LD50	5.580 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	LD50	3.129 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	12.126 mg/kg	rabbit	not specified
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
ethylbenzene 100-41-4	LD50	15.433 mg/kg	rabbit	not specified
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Toluene 108-88-3	LD50	> 5.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	LC50	11 mg/l	vapour	4 h	rat	not specified
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	LC50	> 4,951 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
ethylbenzene 100-41-4	LC50	17,2 mg/l	vapour	4 h	rat	not specified
Toluene 108-88-3	LC50	28,1 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	moderately irritating		rabbit	not specified
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	slightly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
ethylbenzene 100-41-4	moderately irritating	24 h	rabbit	not specified
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	irritating			not specified
Toluene 108-88-3	irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	not irritating		In vitro	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
ethylbenzene 100-41-4	slightly irritating		rabbit	not specified
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	not irritating			not specified
Toluene 108-88-3	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	Category II		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Xylene - mixture of isomeres 1330-20-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	sensitising		mouse	OECD Guideline 442B (Skin Sensitisation: LLNA-BRDU-ELISA/-FCM)
Toluene 108-88-3	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	sensitising		guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Xylene - mixture of isomeres 1330-20-7	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ethylbenzene 100-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
ethylbenzene 100-41-4	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
ethylbenzene 100-41-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ethylbenzene 100-41-4	negative	sister chromatid exchange assay in mammalian cells	with and without		not specified
Toluene 108-88-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Toluene 108-88-3	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Xylene - mixture of isomers 1330-20-7	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	not carcinogenic	inhalation: vapour	6 hours plus T90 (12 minutes) 5 days per week for 105 weeks	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
ethylbenzene 100-41-4	carcinogenic	inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Toluene 108-88-3	not carcinogenic	inhalation: vapour	103 w 6.5 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
ethylbenzene 100-41-4	NOAEL P 1000 ppm NOAEL F1 100 ppm	One generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
ethylbenzene 100-41-4	NOAEL P 500 ppm NOAEL F1 500 ppm NOAEL F2 500 ppm	Two generation study	inhalation	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Toluene 108-88-3	NOAEL P 7500 mg/m ³ NOAEL F1 1875 mg/m ³ NOAEL F2 1875 mg/m ³	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Toluene 108-88-3	NOAEL P 2261 mg/m ³ NOAEL F1 2261 mg/m ³	fertility	inhalation: vapour	rat	not specified

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Xylene - mixture of isomeres 1330-20-7	NOAEL 150 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	NOAEL >= 1.000 mg/kg	oral: gavage	7 days/week	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reprod./Develop. Tox. Screening Test)
ethylbenzene 100-41-4	NOAEL 75 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	NOAEL 12,5 mg/kg			rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Toluene 108-88-3	NOAEL 625 mg/kg	oral: gavage	13 w daily, 5 d/w	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)
Toluene 108-88-3	NOAEL 1131 mg/m3	inhalation: vapour	24 m 6.5 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Toluene 108-88-3	NOAEL 2355 mg/m3	inhalation: vapour	15 w 6.5 h/d, 5 d/w	rat	EU Method B.29 (Sub- Chronic Inhalation Toxicity Test:90-Day Repeated Inhalation Dose Study Using Rodent Species)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	0,9 mm2/s	40 °C	calculated	
ethylbenzene 100-41-4	0,641 mm2/s	40 °C	OECD Test Guideline 114	
Toluene 108-88-3	0,57 mm2/s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Xylene - mixture of isomers 1330-20-7	NOEC	> 1,3 mg/l	56 d	Oncorhynchus mykiss	other guideline:
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	LL50	> 10 - < 30 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
ethylbenzene 100-41-4	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Toluene 108-88-3	NOEC	3,2 mg/l	28 d	Cyprinodon variegatus	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Toluene 108-88-3	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC50	3,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	EL50	> 22 - < 46 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ethylbenzene 100-41-4	EC50	> 1,8 - 2,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	EC50	< 1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Toluene 108-88-3	EC50	3,78 mg/l	48 h	Ceriodaphnia dubia	other guideline:

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	other guideline:
ethylbenzene 100-41-4	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	OECD 211 (Daphnia magna, Reproduction Test)
Toluene 108-88-3	NOEC	0,74 mg/l	7 d	Ceriodaphnia dubia	other guideline:

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC50	4,36 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC10	1,9 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C10, n- alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C10, n- alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	NOELR	< 1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	EC50	7,7 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	NOEC	4,5 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18-unsatd., dimers, reaction products with coco alkyl amine 68647-95-0	EC50	0,39 mg/l	72 h		OECD Guideline 201 (Alga, Growth Inhibition Test)
Toluene 108-88-3	IC50	12 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	NOEC	0,1506 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	EC50	0,6542 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ethylbenzene 100-41-4	EC50	> 152 mg/l	30 min	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Toluene 108-88-3	NOEC	29 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Xylene - mixture of isomers 1330-20-7	readily biodegradable	aerobic	90 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C9-C10, n- alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
ethylbenzene 100-41-4	readily biodegradable	aerobic	69 %	33 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Toluene 108-88-3	readily biodegradable	aerobic	80 %	20 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	readily biodegradable	aerobic	60 %	10 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Xylene - mixture of isomers 1330-20-7	25,9	56 d		Oncorhynchus mykiss	not specified
ethylbenzene 100-41-4	1	42 d	10 °C	Oncorhynchus kisutch	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Toluene 108-88-3	90	3 d		Leuciscus idus melanotus	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Xylene - mixture of isomers 1330-20-7	3,16	20 °C	not specified
ethylbenzene 100-41-4	3,6	20 °C	EU Method A.8 (Partition Coefficient)
Toluene 108-88-3	2,73	20 °C	EU Method A.8 (Partition Coefficient)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	4,68		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Xylene - mixture of isomers 1330-20-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
ethylbenzene 100-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Toluene 108-88-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hexanoic acid, 2-ethyl-, cobalt(2+) salt 136-52-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information
--

14.1. UN number

ADR	1139
RID	1139
ADN	1139
IMDG	1139
IATA	1139

14.2. UN proper shipping name

ADR	COATING SOLUTION
RID	COATING SOLUTION
ADN	COATING SOLUTION
IMDG	COATING SOLUTION
IATA	Coating solution

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	37,6 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H350 May cause cancer.
 H360 May damage fertility or the unborn child.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.