

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 1/(15)

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: multigrade heavy duty engine oil.

Uses advised against: application other than the above.

1.3 Details of the supplier of the safety data sheet:

Trader identification:

UNIX Autó és Alkatrészkereskedelmi Kft.

H-1139 Budapest, Frangepán u. 55-57.

Tel.: 06 1 270 8700

Fax: 06 1 270 8799

E-mail: cs@unixauto.com

Technical information:

UNIX Autó és Alkatrészkereskedelmi Kft.

H-1139 Budapest, Frangepán u. 55-57.

Tel.: 06 1 270 8700

Fax: 06 1 270 8799

E-mail: cs@unixauto.com

Responsible for SDS:

UNIX Autó és Alkatrészkereskedelmi Kft.

H-1139 Budapest, Frangepán u. 55-57.

Tel.: 06 1 270 8700

Fax: 06 1 270 8799

E-mail: cs@unixauto.com

1.4 Emergency telephone number

Emergency telephone (07-15²⁰ h): 06 1 270 8700 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary).

+36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

Hazard Class and Category:

Aquatic Chronic 3

Hazard statement:

H412

Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 2/(15)

2.2 Label elements

Product identification: Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Hazardous component(s): -

GHS Pictogram: -
Signal word: -

Hazard statement:
H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information:
EUH208 Contains Calcium long-chain (C20-26) alkaryl sulfonate, Calcium long chain alkaryl sulfonate and Benzenesulfonic acid, mono-C16-24-alkyl derivs, calcium salts. May produce an allergic reaction.

Precautionary statements – General: -

Precautionary statements – Prevention:
P273 Avoid release to the environment.

Precautionary statements – Response: -

Precautionary statements – Storage: -

Precautionary statements – Disposal:
P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 3/(15)

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Distillates (petroleum), solvent-dewaxed heavy paraffinic* REACH Registr. Nr.: 01-2119471299-27	265-169-7	64742-65-0	- (Note L)	-	max. 90
Distillates (petroleum), solvent-dewaxed light paraffinic REACH Registr. Nr.: 01-2119480132-48	265-159-2	64742-56-9	Asp. Tox. 1 (Note L)	H304	max. 10
Mineral oil raffinate mixture	mixture	mixture	- (Note L)	-	max. 7.0
Mineral oil raffinate mixture**	mixture	mixture	Asp. Tox. 1 (Note L)	H304	max. 6.0
Distillates (petroleum), hydrotreated heavy paraffinic* REACH Registr. Nr.: 01-2119484627-25	265-157-1	64742-54-7	- (Note L)	-	max. 6.0
Zinc alkyl dithiophosphate*** REACH Registr. Nr.: 01-2119657973-23	272-238-5	68784-31-6	Eye Dam. 1 Aquatic Chronic 2	H318 H411	max. 1.3
Calcium long-chain (C20-26) alkaryl sulfonate**** REACH Registr. Nr.: polymer	polymer	722503-69-7	Skin Sens 1B	H317	max. 1.3
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts*** REACH Registr. Nr.: 01-2119493626-26	283-392-8	84605-29-8	Skin Irrit. 2 Eye Dam. 1 Aquatic Chronic 2	H315 H318 H411	max. 1.1
Calcium long chain alkaryl sulfonate REACH Registr. Nr.: polymer	polymer	722503-68-6	Skin Sens 1B	H317	max. 0.70

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 4/(15)

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts REACH Registr. Nr.: 01-2119492616-28	274-263-7	70024-69-0	Skin Sens. 1B	H317	max.0.6
O,O,O-triphenyl phosphorothioate	209-909-9	597-82-0	Repr. 2	H361fd	max.0.11
Phenol, (tetrapropenyl) derivatives***** REACH Registr. Nr.: no data	616-100-8	74499-35-7	Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H314 H318 H360F H400 (M=10) H410 (M=10)	<0.05
Phenol, dodecyl-, branched**** REACH Registr. Nr.: 01-2119513207-49	310-154-3	121158-58-5	Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H314 H318 H360F H400 (M=10) H410 (M=10)	<0.04

*: with exposure limit

** The mixture contains one or more of the following substances:

EC number: 265-157-1 REACH Registration number: 01-2119484627-25

EC number: 265-169-7 REACH Registration number: 01-2119471299-27

EC number: 265-158-7 REACH Registration number: 01-2119487077-29

EC number: 265-159-2 REACH Registration number: 01-2119480132-48

***The product always contains only one ingredient.

Specific concentration limit:

Skin Irrit. 2; : $6.25\% \leq C \leq 100\%$;

Eye Irrit. 2; : $10\% < C \leq 12.5\%$; Eye Dam. 1; : $12.5\% < C \leq 100\%$

**** Specific concentration limit: Skin Sens 1; $C > 1,3\%$

***** The product always contains only one ingredient.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 5/(15)

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. In case of a complaint, call medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of a complaint, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of a complaint, get medical attention.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

Protection of first-aid person: No data available.

4.2 Most important symptoms and effects, both acute and delayed

Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on individual sensitivity.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Not required.

SECTION 5 Fire-fighting measures

Fire hazards:

Combustible.

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, sulphur oxides, phosphor oxides, various hydrocarbons and soot can be formed.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 6/(15)

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil

Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.
Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 7/(15)

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C.

7.3 Specific end use(s)

Multigrade heavy duty engine oil.

SECTION 8 Exposure controls / personal protection

8.1 Control parameters:

Mineral oil mist: TWA: **5 mg/m³**; STEL: 10 mg/m³, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Engineering control measures:

Not required.

Personal protection:

(a) Eye/face protection Where splashing is possible, wear safety glasses (EN 166).

(b) Skin protection

(i) Hand protection Oil resistant gloves (EN 374, Breakthrough time > 480 min, PK power level: 6; PR flow rate: 0).

Note: Manufacturer's directions for use and the conditions of application should be observed.

(ii) Other Protective clothing (oil resistant).

(c) Respiratory protection Under normal conditions not required. In case of exceeded exposure-limits respiratory protection with particle-filter is recommended.

(d) Thermal hazards No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 8/(15)

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state:	liquid
b) Colour:	brown, clear
c) Odour:	characteristic
d) Melting point/freezing point (Pour point) (ISO 3016):	typ. -30°C
e) Boiling point or initial boiling point and boiling range (DIN 51356):	not available
f) Flammability:	combustible
g) Lower and upper explosion limit:	not available
h) Flash point (COC) (EN ISO 2592):	typ. 225°C
i) Auto-ignition temperature:	not available
j) Decomposition temperature:	not available
k) pH:	not applicable
l) Kinematic viscosity (EN ISO 3104) at 40°C:	typ. 113.5 mm ² /s
at 100°C:	typ. 14.7 mm ² /s
m) Solubility Solubility in water:	practically insoluble in water
Solubility in other solvents:	gasoline, kerosene, toluene, etc.
n) Partition coefficient n-octanol/water (log value):	not available
o) Vapour pressure at 20°C:	negligible
p) Density and/or relative density at 15°C (EN ISO 12185):	0.870 – 0.890 g/cm ³
q) Relative vapour density:	not available
r) Particle characteristics:	not available

9.2 Other information

no data available

SECTION 10 Stability and reactivity

10.1 Reactivity:	Dangerous reactivity not known.
10.2 Chemical stability:	No decomposition if stored and handled properly.
10.3 Possibility of hazardous reactions:	Not known.
10.4 Conditions to avoid:	Direct heat or ignition sources.
10.5 Incompatible materials:	Strong oxidizing agents.
10.6 Hazardous decomposition products:	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 9/(15)

SECTION 11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met

Oral:	LD ₅₀ (rat)	> 2000 mg/kg	(based on components)
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg	(based on components)

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Oral:	LD ₅₀ (rat)	> 5000 mg/kg
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg
Inhalation:	LC ₅₀ (rat)	> 5.53 mg/L

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)

Oral:	LD ₅₀ (rat)	> 5000 mg/kg	(literature data)
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg	(literature data)
Inhalation:	LC ₅₀ (rat)	> 5.53 mg/L (4 h)	(literature data)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

Oral:	LD ₅₀ (rat)	> 2000 mg/kg	OECD 401
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg	OECD 402
Inhalation:	LC ₅₀ (rat)	> 5000 mg/m ³	OECD 403

Phenol, (tetrapropenyl) derivatives (CAS: 74499-35-7)

Oral:	LD ₅₀ (rat)	2200 mg/kg	OECD 401
Dermal:	LD ₅₀ (rabbit)	15 000 mg/kg	OECD 402

Skin corrosion/irritation:	Based on available data, the classification criteria are not met.
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation:	Based on available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive toxicity:	Based on available data, the classification criteria are not met.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.

11.2 Information on other hazards

No data.

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 10/(15)

SECTION 12 Toxicological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Fishes:	LC ₅₀	> 100 mg/L
Daphnia:	EC ₅₀	> 100 mg/L
Other aquatic organisms:	EC ₅₀	> 100 mg/L
Other living beings:	TLM	> 1 mg/L

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)

Fishes:	LC ₅₀	> 100 mg/L
Other aquatic organisms:	EC ₅₀	> 100 mg/L
Algae:	ErC ₅₀	> 100 mg/L
Crustacea:	NOEC	> 1 mg/L

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

Fish:	> 1000 mg/L	96 h (OECD 203)
Daphnia:	> 100 mg/L	48 h (OECD 202)
Algae:	> 100 mg/L	72 h (OECD 201)

Zinc-alkyl-dithiophosphate (CAS: 84605-29-8)

Fish (Oncorhynchus mykiss):	LC ₅₀	4,5 mg/L	96 h
Fish (Mutton-headed carp):	LC ₅₀	46 mg/L	96 h
Fish (Oncorhynchus mykiss):	NOEC	1.8 mg/L	96 h
Daphnia:	EC ₅₀	23 mg/L	48 h
Daphnia:	EC ₅₀	> 0.8 mg/L	21 days
Daphnia:	NOEC	10 mg/L	48 h
Daphnia:	NOEC	0.4 mg/L	21 days
Green algae:	EC ₅₀	21 mg/L	72 h
Green algae:	NOEC	10 mg/L	72 h

Phenol, (tetrapropenyl) derivatives (CAS: 74499-35-7)

Fish (Rainbow trout):	LC ₅₀	40 mg/L	96 h
Daphnia:	EC ₅₀	0.037 mg/L	48 h
Crustacea (Mysidopsis Bahia):	EC ₅₀	> 0.58 mg/L	96 h
Daphnia:	EC ₅₀	0.0079 mg/L	21 days
Daphnia:	NOEC	0.0037 mg/L	21 days
Algae:	EC ₅₀	0.36 mg/L	72 h

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 11/(15)

Phenol, dodecyl-, branched (CAS: 121158-58-5)

Fish (Fat-headed carp):	LC ₅₀	40 mg/L	96 h
Daphnia:	EC ₅₀	0.037 mg/L	48 h
Crustacea (Mysidopsis Bahia):	EC ₅₀	> 0.58 mg/L	96 h
Daphnia:	EC ₅₀	0.0079 mg/L	21 days
Daphnia:	NOEC	0.0037 mg/L	21 days
Algae:	EC ₅₀	0.36 mg/L	72 h
Microorganisms (activated sludge):	EC ₅₀	> 1000 mg/L	0.1 day

12.2 Persistence and degradability

Biodegradability:	Hydrocarbons are inherently degradable.
Zinc -alkyl-dithiophosphate	1.5 % (28 days, OECD TG 301B)
Phenol, (tetrapropenyl) derivatives	25 % (28 days, OECD TG 301 B)
Phenol, dodecyl-, branched	25 % (28 days, OECD TG 301 B)

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

Absorbs in soil.

Mobility in water:

Floats on water.

12.5 Results of PBT and vPvB assessment

Does not contain PBT and vPvB substances.

12.6 Endocrine disrupting properties

No data.

12.7 Other adverse effects

Heavy metal content: None.

PCT, PCB and other chlorinated hydrocarbons:

None.

Environmental effects:

Spills may form a film on water surfaces causing impaired oxygen transfer.

Water hazard class (German):

WGK 2 (Classification by AwSV).

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Recommended waste treatment method: incineration

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 12/(15)

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

SECTION 14 Transport information

Land transport:

Road/ Railway

ADR/RID:

Not classified.

14.1 UN number or ID number:

Not classified.

14.2 UN proper shipping name:

Not classified.

14.3 Transport hazard class(es):

Not classified.

14.4 Packing group:

Not classified.

14.5 Environmental hazards:

Not classified.

14.6 Special precautions for user:

Not classified.

Waterways:

Inland waterways/ Sea transport

ADN/IMDG:

Not apply to the product.

Air transport: ICAO / IATA:

Not apply to the product.

SECTION 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008.

Seveso category: not classified.

15.2 Chemical safety assessment.

not available

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 13/(15)

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Aquatic Chronic 3 H412 calculation method

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1	Aspiration hazard Category 1
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens 1B	Respiratory/skin sensitization Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, Chronic Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meisterteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 14/(15)

Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification and Labelling
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ec _x	Effective Concentration x%
ErC ₅₀	EC ₅₀ in terms of reduction of growth rate
Ed _x	Effective Dose x%
EC	European Community
EC number	European Community number
ELINCS	European List of Notified Chemical Substances
ES	Exposure Scenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC _x	Lethal Concentration x%
LD _x	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts/million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International carriage of Dangerous Goods by Rail

SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **A.Z. Meistererteile Motorenöl MT-Truck 15W-40 Plus**

Version: 3

Latest revision: 03. 03. 2022

Date of issue: 24. 10. 2017

Page: 15/(15)

SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

Revision Indicators:

Section	Subject of change	Date	Version
1-16	Full revision due to composition change Revision modification according to 2020/878/EU	03. 06. 2021	2
3	Composition/information on ingredients	03. 03. 2022	3
11	Toxicological information		
12	Toxicological information		