according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 1/(17)

## SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

#### A.Z. Meisterteile Getriebeöl GL-5 80W-90

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: automotive gear oil

Uses advised against: application other than the above.

1.3 Details of the supplier of the safety data sheet:

Trader identification: Technical information:

UNIX Autó és Alkatrészkereskedelmi Kft. UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. H-1139 Budapest, Frangepán u. 55-57.

Tel.: +36 1 270 8700

Fax: +36 1 270 8799

E-mail: cs@unixauto.com

Tel.: +36 1 270 8700

Fax: +36 1 270 8799

E-mail: cs@unixauto.com

E-mail: cs@unixauto.com

Responsible for SDS:

UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57.

Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

1.4 Emergency telephone number

Emergency telephone (07-15<sup>20</sup> h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary). +36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

#### **SECTION 2** Hazards identification

2.1 Classification of the substance or mixture

Hazard Class and Category: Hazard statement:

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 2/(17)

2.2 Label elements

Product identification: Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Hazardous component(s): Amines, C10-C14-tert-alkyl

GHS Pictogram:

❖

Signal word: Warning

Hazard statement:

**H317** May cause an allergic skin reaction.

**H412** Harmful to aquatic life with long lasting effects.

Supplemental hazard information: -

Precautionary statements – General:

**P101** If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements – Prevention:

**P273** Avoid release to the environment.

**P280** Wear protective gloves.

Precautionary statements – Response:

P302 + P352 IF ON SKIN: Wash with plenty of soapy water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Precautionary statements – Storage: -

Precautionary statements – Disposal:

**P501** Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006, at a concentration of 0.1% or more.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-580W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 3/(17)

The mixture does not contain any substance with endocrine disrupting properties, at a concentration of 0.1% or more.

## **SECTION 3** Composition/information on ingredients

#### 3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EC	CAS	Hazard classes and	Hazard	Conc.
Name	number	number	cat.	statements	%(m/m)
Distillates (petroleum),	265-169-7	64742-65-0	-	-	max.95
solvent-dewaxed heavy			(Note L)		
paraffinic*					
REACH Registr. Nr.:					
01-2119471299-27					
Lubricatingoils	309-877-7	101316-72-7		-	max.80
(petroleum), C24-50,			(Note L)		
solvent-extd., dewaxed,					
hydrogenated*					
REACH Registr. Nr.:					
01-2119489969-06	265 157 1	64740 547			
Distillates (petroleum), hydrotreated heavy	265-157-1	64742-54-7	(Note L)	-	max.80
paraffinic			(Note L)		
REACH Registr. Nr.:					
01-2119484627-25					
Lubricating oils*	278-012-2	74869-22-0	-	_	max.80
REACH Registr. Nr.:	270 012 2	, .00, 22 0	(Note L)		
01-2119495601-36			,		
Distillates (petroleum),	265-090-8	64741-88-4	-	-	max.65
solvent-refined heavy			(Note L)		
paraffinic*					
REACH Registr. Nr.:					
01-2119474878-16					
Residual oils (petroleum),	265-166-0	64742-62-7	-	-	max.50
solvent-dewaxed			(Note L)		
REACH Registr. Nr.:					
01-2119480472-38					
Residual oils (petroleum),	265-101-6	64742-01-4	-	-	max.40
solvent-refined*			(Note L)		
REACH Registr. Nr.:					
01-2119488707-21					

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 4/(17)

	EC	CAC	Howard along and	Howard	Como
Name	EC	CAS	Hazard classes and	Hazard	Conc.
1 (4111)	number	number	cat.	statements	%(m/m)
Amines, C10-C14-tert-	701-175-2	-	Acute Tox. 4	H302	< 0.12
alkyl			Acute Tox. 3	H311	
REACH Registr. Nr.:			Skin Corr. 1B	H314	
01-2119456798-18			Skin Sens. 1 A	H317	
			Eye Dam. 1	H318	
			Acute Tox. 2	H330	
			STOT SE 3	H335	
			Aquatic Acute 1	H400 (M=1)	
			Aquatic Chronic 1	H410 (M=1)	
C16-18-(even numbered,	627-034-4	1213789-63-9	Acute Tox. 4	H302	< 0.08
saturated and			Skin Corr. 1B	H314	
unsaturated)-alkylamines			Eye Dam. 1	H318	
REACH Registr. Nr.:			STOT SE 3	H335	
01-2119473797-19			STOT RE 2	H373	
			Asp. Tox. 1	H304	
			Aquatic Acute 1	H400 (M=10)	
			Aquatic Chronic 1	H410 (M=10)	

<sup>\*:</sup> with exposure limit

#### Note L:

The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

The full text of each relevant H-phrase and Hazard classes and cat. see in Section 16.

#### **SECTION 4** First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain

medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use

soap. In case of persistent irritation, get medical attention.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 5/(17)

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent

irritation, get medical attention.

Ingestion: If swallowed, give water. Do not induce vomiting. Get medical attention.

Protection of first-aid person: No data available.

4.2 Most important symptoms and effects, both acute and delayed

Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on individual sensitivity.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed Not required.

## **SECTION 5** Fire-fighting measures

Fire hazards:

Combustible.

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire-fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 6/(17)

#### **SECTION 6** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be removed. Recover free liquid by

pumping. Contain the rest or small quantities with sand, earth or other

suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable

absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

#### **SECTION 7** Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well-ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Automotive gear oil.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 7/(17)

#### **SECTION 8** Exposure controls / personal protection

8.1 Control parameters:

Mineral oil mist: TWA: 5 mg/m<sup>3</sup>; STEL: 10 mg/m<sup>3</sup>, for oil mist, vapour

excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Engineering control measures:

Not required.

Personal protection:

(a) Eye/face protection Where splashing is possible, wear safety glasses (EN 166).

(b) Skin protection

(i) Hand protection Oil resistant gloves (EN 374, Breakthrough time > 480 min, PK

power level: 6; PR flow rate: 0).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

(ii) Other Protective clothing (oil resistant).

(c) Respiratory protection Under normal conditions not required. In case of exceeded

exposure-limits respiratory protection with particle-filter is

recommended.

(d) Thermal hazards No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

#### **SECTION 9** Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state: liquid

b) Colour:c) Odour:dour:dour:brown, clear characteristic

d) Melting point/freezing point (Pour point) (ISO 3016): typ. -27°C

e) Boiling point or initial boiling point and boiling range

(DIN 51356): not available

f) Flammability: combustible

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 8/(17)

g) Lower and upper explosion limit:
h) Flash point (COC) (EN ISO 2592):
typ. 230°C
not available
j) Decomposition temperature:
not available
pH:
not applicable

1) Kinematic viscosity (EN ISO 3104):

at 40°C: typ. 143.0 mm<sup>2</sup>/s at 100°C: typ. 14.6 mm<sup>2</sup>/s

m) Solubility

Solubility in water: practically insoluble in water Solubility in other solvents: gasoline, kerosene, toluene, etc.

n) Partition coefficient n-octanol/water (log value): not available o) Vapour pressure at 20°C: negligible

p) Density and/or relative density at 15°C (EN ISO 12185): 0.885 – 0.905 g/cm<sup>3</sup>

q) Relative vapour density: not availabler) Particle characteristics: not available

9.2 Other information no data available

## SECTION 10 Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous reactions: Not known.

10.4 Conditions to avoid: Direct heat or ignition sources.10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition products: No dangerous decomposition products are formed under

normal conditions. Hazardous combustion products: See

Section 5.

# **SECTION 11** Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Based on available data, the classification criteria are not met

 $\begin{array}{lll} \text{Oral:} & \text{LD}_{50} \text{ (rat)} & >2000 \text{ mg/kg} & \text{(based on components)} \\ \text{Dermal:} & \text{LD}_{50} \text{ (rabbit)} & >2000 \text{ mg/kg} & \text{(based on components)} \end{array}$ 

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-580W-90

Version: 3 Latest revision: 16, 06, 2022 Date of issue: 02.11.2017 Page: 9/(17)

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Oral: LD<sub>50</sub> (rat) > 5000 mg/kgDermal: LD<sub>50</sub> (rabbit) > 5000 mg/kgInhalation:  $LC_{50}$  (rat) > 5.00 mg/L (4 h)

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated

(CAS: 101316-72-7)

Oral: LD<sub>50</sub> (rat) > 5000 mg/kg**OECD 401** Dermal:  $LD_{50}(rat)$ > 5000 mg/kg**OECD 402**  $LC_{50}$  (rat) > 5.0 mg/L (4 h)**OECD 403** Inhalation:

Distillates (petroleum), solvent-refined heavy paraffinic (CAS: 64741-88-4)

> 5000 mg/kg**OECD 401** Oral:  $LD_{50}$  (rat) Dermal: LD<sub>50</sub> (rabbit) > 5000 mg/kg**OECD 402** Inhalation: LC<sub>50</sub> (rat) > 5.53 mg/L (4 h) **OECD 403** 

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

> 5000 mg/kgOral:  $LD_{50}$  (rat) Dermal: LD<sub>50</sub> (rabbit) > 5000 mg/kg> 5.00 mg/L (4 h)Inhalation:  $LC_{50}$  (rat)

Lubricating oils (CAS: 74869-22-0)

Oral: LD<sub>50</sub> (rat) > 5000 mg/kg**OECD 401** Dermal: LD<sub>50</sub> (rabbit) > 5000 mg/kg**OECD 402** > 5.53 mg/L (4 h) **OECD 403** Inhalation:  $LC_{50}$  (rat)

Residual oils (petroleum), solvent-dewaxed (CAS: 64742-62-7)

LD<sub>50</sub> (rat) > 5000 mg/kg**OECD 401** Oral: Dermal: LD<sub>50</sub> (rabbit) > 5000 mg/kg**OECD 402** Inhalation: LC<sub>50</sub> (rat) > 5.53 mg/L (4 h) **OECD 403** 

Residual oils (petroleum), solvent-refined (CAS: 64742-01-4):

> 5000 mg/kgOral: LD<sub>50</sub> (rat) **OECD 401** > 5000 mg/kgDermal: LD<sub>50</sub> (rat) **OECD 402** > 5.0 mg/L/4 h**OECD 403** Inhalation: LC<sub>50</sub> (rat)

Amines, C10-C14-tert-alkyl (EC: 701-175-2)

LD<sub>50</sub> (rat) Oral: 612 mg/kgDermal: LD<sub>50</sub> (rat) 251 mg/kgInhalation:  $LC_{50}$  (rat) 157 ppm (4 h)

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 10/(17)

C16-18-(even numbered, saturated and unsaturated)-alkylamines (CAS: 1213789-63-9):
Oral: LD<sub>50</sub> (rat) 1689 mg/kg OECD 401

Skin corrosion/irritation:
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity:

Carcinogenicity:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

The mixture does not contain any substance with endocrine disrupting properties, at a concentration of 0.1% or more.

## **SECTION 12** Ecological information

12.1 Toxicity Harmful to aquatic life with long lasting effects.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Fish: LL/EL/IL<sub>50</sub> > 100 mg/LCrustacea: LL/EL/IL<sub>50</sub> > 100 mg/LAlgae: LL/EL/IL<sub>50</sub> > 100 mg/LMicroorganisms: LC/EC/IC<sub>50</sub> > 100 mg/LFish: NOEC/NOEL > 100 mg/L $NOEC/NOEL > 1 - \le 10 \text{ mg/L}$ Crustacea:

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated

(CAS: 101316-72-7)

Fish:  $LC_{50}$  > 100 mg/L (LL50) Daphnia:  $EC_{50}$  > 10 000 mg/L (WAF, 48 h, OECD 202)

Distillates (petroleum), solvent-refined heavy paraffinic (CAS: 64741-88-4)

Fish (Pimephales promelas):  $LC_{50}$  > 100 mg/L 96 h Daphnia (Daphnia magna):  $EL_{50}$  > 10 000 mg/L 48 h

Daphnia (Daphnia magna): NOEC 0.02 mg/L

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-580W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 11/(17)

Algae (Pseudokirchneriella subcapitata): Activated sludge	NOEL	> 100 mg/	L 72 h			
(Photobacterium phosphoreum):	NOEL	1.93 mg/	L 96 h			
Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)						
Fish (Pimephales promelas):	NOEL	≥ 100 mg/	L 96 h			
Fish (Oncorhynchus mykiss):	NOEL	> 1000  mg/s				
Daphnia (Daphnia magna):	NOEL	> 10000 mg/				
Daphnia (Daphnia magna):	NOEL	> 100 mg/				
Algae		_	•			
(Pseudokirchinella subcapitata):	NOEL	$\geq 100 \text{ mg/s}$	L 72 h			
Lubricating oils (CAS: 74869-22-0)						
Fish:	$LL_{50}$	≥ 100 mg/	L 96 h			
Fish:	NOEL	$\geq 100 \text{ mg/s}$				
Daphnia (Daphnia magna):	$EL_{50}$	> 10000 mg/				
		J	(OECD 2			
Daphnia (Daphnia magna):	NOEL	> 1000  mg/s	L 48 h			
Daphnia (Daphnia magna):	NOEL	10 mg/				
Algae:	NOEL	≥ 100 mg/	L 72 h			
Algae:	NOEL	≥ 100 mg/				
		·				
Residual oils (petroleum), solvent-dewax	xed (CAS: 6474	12-62-7)	(OECD 2			
		·	(OECD 2 L 96 h			
Residual oils (petroleum), solvent-dewax	xed (CAS: 6474 LL <sub>50</sub>	42-62-7) > 100 mg/	(OECD 2 L 96 h (OECD 2			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish:	xed (CAS: 6474 LL <sub>50</sub> NOEL	12-62-7) > 100 mg/ ≥ 100 mg/	(OECD 2) L 96 h (OECD 2) L			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):	xed (CAS: 6474 LL <sub>50</sub>	42-62-7) > 100 mg/	(OECD 2) L 96 h (OECD 2) L L 48 h			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish: Daphnia (Daphnia magna):	xed (CAS: 6474 LL <sub>50</sub> NOEL	22-62-7) > 100 mg/s ≥ 100 mg/s > 10 000 mg/s	(OECD 2 L 96 h (OECD 2 L L 48 h (OECD 2			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish:	xed (CAS: 6474 LL <sub>50</sub> NOEL EL <sub>50</sub>	12-62-7) > 100 mg/ ≥ 100 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish: Daphnia (Daphnia magna): Daphnia:	xed (CAS: 6474 LL <sub>50</sub> NOEL EL <sub>50</sub> NOEL	2-62-7) > 100 mg/ ≥ 100 mg/ > 10 000 mg/ ≥ 1000 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L L L 21 days			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish: Daphnia (Daphnia magna): Daphnia: Daphnia:	NOEL NOEL NOEL NOEL NOEL NOEL NOEL NOEL	2-62-7) > 100 mg/ ≥ 100 mg/ > 10 000 mg/ ≥ 1000 mg/ 10 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L 21 days (OECD 2			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas): Fish: Daphnia (Daphnia magna): Daphnia:	xed (CAS: 6474 LL <sub>50</sub> NOEL EL <sub>50</sub> NOEL	2-62-7) > 100 mg/ ≥ 100 mg/ > 10 000 mg/ ≥ 1000 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L 21 days (OECD 2)  L 96 h			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):  Fish: Daphnia (Daphnia magna):  Daphnia: Daphnia: Cammarus pulex:	NOEL NOEL NOEL NOEL NOEL NOEL NOEL NOEL	2-62-7) > 100 mg/ ≥ 100 mg/ > 10 000 mg/ ≥ 1000 mg/ 10 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L 21 days (OECD 2  L 96 h (OECD 2)			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):  Fish: Daphnia (Daphnia magna):  Daphnia: Daphnia: Gammarus pulex:  Aquatic invertebrates:	NOEL EL <sub>50</sub> NOEL EL <sub>50</sub> NOEL NOEL LL <sub>50</sub>	2-62-7)  > 100 mg/  ≥ 100 mg/  > 10 000 mg/  10 mg/  > 10 000 mg/  > 10 mg/	(OECD 2  L 96 h (OECD 2  L 48 h (OECD 2  L 21 days (OECD 2  L 96 h (OECD 2			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):  Fish: Daphnia (Daphnia magna):  Daphnia: Daphnia: Cammarus pulex:	NOEL EL <sub>50</sub> NOEL EL <sub>50</sub> NOEL NOEL LL <sub>50</sub>	2-62-7)  > 100 mg/  ≥ 100 mg/  > 10 000 mg/  10 mg/  > 10 000 mg/  > 10 000 mg/  > 10 000 mg/	(OECD 2  L 96 h (OECD 2  L 48 h (OECD 2  L 21 days (OECD 2  L 96 h (OECD 2			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):  Fish: Daphnia (Daphnia magna):  Daphnia: Daphnia: Cammarus pulex:  Aquatic invertebrates: Algae	NOEL EL50 NOEL NOEL NOEL NOEL NOEL NOEL NOEL NOEL	2-62-7)  > 100 mg/  ≥ 100 mg/  > 10 000 mg/  10 mg/  > 10 000 mg/  > 10 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L 21 days (OECD 2)  L 96 h (OECD 2)  L 72 h			
Residual oils (petroleum), solvent-dewax Fish (Pimephales promelas):  Fish: Daphnia (Daphnia magna):  Daphnia: Daphnia: Cammarus pulex:  Aquatic invertebrates: Algae	NOEL EL50 NOEL NOEL NOEL NOEL NOEL NOEL NOEL NOEL	2-62-7)  > 100 mg/  ≥ 100 mg/  > 10 000 mg/  10 mg/  > 10 000 mg/  > 10 000 mg/  > 10 000 mg/	(OECD 2)  L 96 h (OECD 2)  L 48 h (OECD 2)  L 21 days (OECD 2)  L 96 h (OECD 2)			

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-580W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 12/(17)

Residual oils (petroleum), solvent-refined (CAS: 64742-01-4):						
	Fishes:	$LL_{50}$	> 100	mg/L		
	Daphnia:	EC <sub>50</sub>	> 10 000	mg/L	(48 h, OECD 202)	
	Amines, C10-14-tert-alkyl (EC: 701-175-2	)				
	Fish (Oncorhynchus mykiss):	$LL_{50}$	1,3	mg/L	96 h	
	Fish (Oncorhynchus mykiss):	NOEC	0.078	mg/L	96 h	
	Daphnia (Daphnia magna):	$EL_{50}$	2.5	mg/L	48 h	
	Algae					
	(Pseudokirchneriella subcapitata):	$EL_{50}$	0.44	mg/L	72 h	
	Algae			_		
	(Pseudokirchneriella subcapitata):	NOEL	0.05	mg/L	72 h	
	Microorganisms (activated sludge):	$EL_{50}$	63.5	mg/L	30 min	
	C16-18-(even numbered, saturated and un	•				
	Algae	$EL_{50}$	0.04	mg/L	96 h	
	(Selenastrum capricornutum):		0.011	/*	40.1	
	Daphnia magna:	$EL_{50}$		mg/L	48 h	
	Microorganisms:	$EL_{50}$		mg/L	3 h	
	Fish (Pimephales promelas):	LL <sub>50</sub>		mg/L	96 h	
	Algae (Selenastrum capricornutum):	NOEL		mg/L	96 h	
	Daphnia magna:	NOEL	0.013	mg/L	21 days	
12.2	Persistence and degradability					
	Biodegradability:	Hydrocarbons are inherently degradable.				
	Amines, C10-14-tert-alkyl					
	(EC: 701-175-2)	21.8% (28 days, OECD 301 D)				
	C16-18-(even numbered, saturated and					
	unsaturated)-alkylamines					
	(CAS: 1213789-63-9)	66% (28 days, OECD 301 B)				
12.3	Bioaccumulative potential	No data availab	le.			
12.0	Amines, C10-14-tert-alkyl	110 0000 01 00100				
	(EC: 701-175-2)	Log Pow: 2.9 (1	ow)			
	·		•			
12.4	Mobility in soil	Absorbs in soil.				
	Mobility in water:	Floats on water.	•			

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 13/(17)

12.5 Results of PBT and vPvB assessment Does not contain PBT and vPvB substances, at a

concentration of 0.1% or more.

12.6 Endocrine disrupting properties The mixture does not contain any substance with

endocrine disrupting properties, at a concentration

of 0.1% or more.

12.7 Other adverse effects

Heavy metal content: None.

PCT, PCB and other chlorinated

hydrocarbons: None.

Environmental effects: Spills may form a film on water surfaces causing

impaired oxygen transfer.

Water hazard class (German): WGK 1 (Classification by AwSV)

## **SECTION 13** Disposal considerations

#### 13.1 Waste treatment methods

#### Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05\*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

#### Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

#### Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 14/(17)

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

#### **SECTION 14** Transport information

Land transport:

Road/Railway ADR/RID: Not classified.

14.1. UN number or ID number: Not classified. 14.2. UN proper shipping name: Not classified. 14.3. Transport hazard class(es): Not classified. 14.4. Packing group: Not classified. Environmental hazards: 14.5. Not classified. Special precautions for user: 14.6. Not classified.

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.

#### **SECTION 15** Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008.

Seveso category: not classified.

15.2 Chemical safety assessment.

not available

#### **SECTION 16** Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Latest revision: 16. 06. 2022 Version: 3 Date of issue: 02. 11. 2017 Page: 15/(17)

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC

(CLP)

Skin Sens. 1 calculated method H317 Aquatic Chronic 3 H412 calculated method

The full text of each relevant H-phrase and Hazard classes and cat. in Section 3.:

The first test of ee	ten ete en in production and trace and trace and the section of
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to kidneys through prolonged or repeated exposure
	if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Acute Tox. 4	Acute toxicity Category 4
Asp. Tox. 1	Aspiration hazard Category 1.
A - ( TD - 2	

Acute Tox. 3 Acute toxicity Category 3

Skin Corr. 1A, 1B Skin corrosion/irritation Category 1A, 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 Respiratory/skin sensitization Category 1A Skin Sens.1A Eve Dam. 1 Serious eye damage/eye irritation Category 1

Acute Tox. 2 Acute toxicity Category 2

Specific target organ toxicity — single exposure Category 3 STOT SE 3 Specific target organ toxicity – repeated exposure Category 2 STOT RE 2

Hazardous to the aquatic environment Category 1. Aquatic Acute 1 Aquatic Chronic 1 Hazardous to the aquatic environment Category 1.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-5 80W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 16/(17)

Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Bioconcentration Factor
BOD Biological Oxygen Demand

Bw Body Weight

C&L Classification and Labelling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR Carcinogenic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand CSA Chemical Safety Assessment

CSR Carcinogenic, Mutagenic or toxic to Reproduction

DMEL Chemical Oxygen Demand
DNEL Derived No Effect Level
ECHA European Chemicals Agency
Ecx Effective Concentration x%

ErC50 EC50 in terms of reduction of growth rate

Edx Effective Dose x% EC European Community

EC number European Community number

ELINCS European List of Notified Chemical Substances

ES Exposure Scenario

IARC International Agency for Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods

LCx Lethal Concentration x%

LDx Lethal Dose x%

LOAEC Lowest Observed Adverse Effect Concentration

LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
NOEC No observed effect concentration

NOEL No observed effect level NLP No-Longer Polymer

NOAEL No Observed Adverse Effect Level

OECD Organisation for Economic Cooperation and Development

PBT Persistent Bioaccumulative and Toxic
PNEC Predicted No-Effect Concentration

ppm parts/million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International carriage of Dangerous Goods by Rail

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Getriebeöl GL-580W-90

Version: 3 Latest revision: 16. 06. 2022 Date of issue: 02. 11. 2017 Page: 17/(17)

SVHC Substance of Very High Concern

UVCB substance of unknown or variable composition, complex reaction products or biological

materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bio-accumulative

# **Revision Indicators:**

Section	Subject of change	Date	Version
2.	Hazards identification	03. 03. 2020	2
3.	Composition/information on ingredients		
11.	Toxicological information		
12.	Ecological information		
1-16.	Full revision due to composition change	16.06.2022	3
	Revision modification according to 2020/878/EU		