



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 25

TEROSON PU 9200 BK

SDS No. : 75920
V016.0

Revision: 12.08.2022
printing date: 12.09.2022

Replaces version from: 08.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON PU 9200 BK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

1-component-polyurethane adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	

2.2. Label elements**Label elements (CLP):**

Hazard pictogram:	
Contains	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 4,4'- methylenediphenyl diisocyanate Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 4-isocyanatosulphonyltoluene dibutyltin dilaurate
Signal word:	Danger
Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure.
Supplemental information	As from 24 August 2023 adequate training is required before industrial or professional use. Further information: https://www.feica.eu/PUinfo
Precautionary statement: Prevention	P260 Do not breathe dust/fume/spray. P280 Wear protective gloves/eye protection.
Precautionary statement: Response	P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	10- 20 %	Acute Tox. 4, Inhalation, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Resp. Sens. 1, H334 STOT SE 3, H335 STOT RE 2, H373	oral:ATE = > 5.000 mg/kg inhalation:ATE = 1,5 mg/l;dust/mist	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics 90622-57-4 918-167-1 01-2119472146-39	5- < 10 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226	dermal:ATE = 2.201 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene 01-2119555267-33	1- < 5 %	Aquatic Chronic 3, H412 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, Dermal, H312 Acute Tox. 4, Inhalation, H332 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373		
4,4'- methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47	0,1- < 1 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 %	
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2 500-060-2 01-2119970543-34	0,1- < 1 %	Skin Sens. 1, H317 STOT SE 3, H335 Acute Tox. 4, Inhalation, H332	inhalation:ATE = 1,5 mg/l;dust/mist	
4-isocyanatosulphonyltoluene 4083-64-1 223-810-8 01-2119980050-47	0,1- < 1 %	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334	Eye Irrit. 2; H319; C >= 5 % STOT SE 3; H335; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
dibutyltin dilaurate 77-58-7 201-039-8 01-2119496068-27	0,1- < 0,25 %	Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Delayed effects possible after inhalation.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a dry place.

Container must be made airtight after use.

Storage at 15 to 25°C is recommended.

7.3. Specific end use(s)

1-component-polyurethane adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Polyvinyl chloride 9002-86-2 [Polyvinyl chloride, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Polyvinyl chloride 9002-86-2 [Polyvinyl chloride, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Di-"isononyl" phthalate 28553-12-0 [Diisononyl phthalate]		5	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
4,4'-Methylenediphenyl diisocyanate		0,02	Time Weighted Average		EH40 WEL

101-68-8 [ISOCYANATES, ALL (AS -NCO)]			(TWA):		
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
p-Toluenesulphonyl isocyanate 4083-64-1 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
p-Toluenesulphonyl isocyanate 4083-64-1 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Dibutyltin dilaurate 77-58-7 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (AS SN)]		0,1	Time Weighted Average (TWA):		EH40 WEL
Dibutyltin dilaurate 77-58-7 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (AS SN)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Dibutyltin dilaurate 77-58-7 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (AS SN)]		0,2	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE (PVC)]		1	Time Weighted Average (TWA):		IR_OEL
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE (PVC)]		10	Time Weighted Average (TWA):		IR_OEL
Di-"isononyl" phthalate 28553-12-0 [Diisononyl phthalate]		5	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5		4	Time Weighted Average (TWA):		IR_OEL

[DUSTS NON-SPECIFIC]					
4,4'-Methylenediphenyl diisocyanate 101-68-8 [4,4'-METHYLENE-DIPHENYL DIISOCYANATE (AS -NCO)]	0,005		Time Weighted Average (TWA):		IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,02	Time Weighted Average (TWA):		IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,02	Time Weighted Average (TWA):		IR_OEL
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
p-Toluenesulphonyl isocyanate 4083-64-1 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
p-Toluenesulphonyl isocyanate 4083-64-1 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,02	Time Weighted Average (TWA):		IR_OEL
Dibutyltin dilaurate 77-58-7 [TIN, ORGANIC COMPOUNDS]		0,2	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Dibutyltin dilaurate 77-58-7 [TIN, ORGANIC COMPOUNDS]		0,1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		0,0037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		0,037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,00037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				11,7 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				1,17 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Soil				2,33 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	sewage treatment plant (STP)		6,46 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	aqua (freshwater)		0,03 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	aqua (marine water)		0,003 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	sewage treatment plant (STP)		0,4 mg/l				
p-Toluenesulphonyl isocyanate 4083-64-1	sediment (freshwater)				0,172 mg/kg		
p-Toluenesulphonyl isocyanate 4083-64-1	sediment (marine water)				0,017 mg/kg		
p-Toluenesulphonyl isocyanate 4083-64-1	Soil				0,017 mg/kg		
dibutyltin dilaurate 77-58-7	aqua (freshwater)		0,000463 mg/l				
dibutyltin dilaurate 77-58-7	aqua (marine water)					0,0463 µg/l	
dibutyltin dilaurate 77-58-7	aqua (intermittent releases)		0,00463 mg/l				
dibutyltin dilaurate 77-58-7	sediment (freshwater)				0,05 mg/kg		
dibutyltin dilaurate 77-58-7	sediment (marine water)				0,005 mg/kg		
dibutyltin dilaurate 77-58-7	Soil				0,0407 mg/kg		
dibutyltin dilaurate 77-58-7	Sewage treatment plant		100 mg/l				
dibutyltin dilaurate 77-58-7	oral				0,2 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	inhalation	Long term exposure - systemic effects		221 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	inhalation	Long term exposure - local effects		221 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	inhalation	Long term exposure - local effects		65,3 mg/m ³	
Reaction mass of ethylbenzene and m-xylene and p-xylene	General population	inhalation	Acute/short term exposure - local effects		260 mg/m ³	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m ³	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m ³	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m ³	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m ³	no potential for bioaccumulation
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	inhalation	Acute/short term exposure - local effects		1 mg/m ³	
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m ³	
p-Toluenesulphonyl isocyanate 4083-64-1	Workers	inhalation	Long term exposure - systemic effects		3,24 mg/m ³	
p-Toluenesulphonyl isocyanate 4083-64-1	Workers	dermal	Long term exposure - systemic effects		0,92 mg/kg	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	inhalation	Long term exposure - systemic effects		0,8 mg/m ³	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	dermal	Long term exposure - systemic effects		0,46 mg/kg	
p-Toluenesulphonyl isocyanate 4083-64-1	General population	oral	Long term exposure - systemic effects		0,46 mg/kg	
dibutyltin dilaurate 77-58-7	Workers	dermal	Acute/short term exposure - systemic effects		2,08 mg/kg	
dibutyltin dilaurate 77-58-7	Workers	Dermal	Long term exposure -		0,43 mg/kg	

			systemic effects			
dibutyltin dilaurate 77-58-7	Workers	inhalation	Long term exposure - systemic effects		0,02 mg/m ³	
dibutyltin dilaurate 77-58-7	General population	dermal	Acute/short term exposure - systemic effects		0,5 mg/kg	
dibutyltin dilaurate 77-58-7	General population	inhalation	Acute/short term exposure - systemic effects		0,04 mg/m ³	
dibutyltin dilaurate 77-58-7	General population	oral	Acute/short term exposure - systemic effects		0,02 mg/kg	
dibutyltin dilaurate 77-58-7	General population	dermal	Long term exposure - systemic effects		0,16 mg/kg	
dibutyltin dilaurate 77-58-7	General population	inhalation	Long term exposure - systemic effects		0,005 mg/m ³	
dibutyltin dilaurate 77-58-7	General population	oral	Long term exposure - systemic effects		0,003 mg/kg	
dibutyltin dilaurate 77-58-7	Workers	inhalation	Acute/short term exposure - systemic effects		0,059 mg/m ³	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		
p-Toluenesulphonyl isocyanate 4083-64-1 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

If intensive ventilation/extraction is not possible respiratory protection equipment with ABEK P2 filter (EN 14387) should be worn.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; \geq 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; \geq 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	solid
Delivery form	paste
Colour	grey
Odor	Faintly, specific
Melting point	Not applicable, Determination technically not possible
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	Not applicable, Decomposes > 140°C (284°F).
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	Not applicable, Product is a solid.
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product reacts with water.
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture < 0,1 hPa
Density (20 °C (68 °F))	1,17 - 1,23 g/cm ³ QP2107.1; Density
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable, mixture is a paste.

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Flammable Solids	
Burning rate	0,26 mm/s
Burning time	580 s; no method

9.2.2. Further safety characteristics**SECTION 10: Stability and reactivity****10.1. Reactivity**Reacts with water: Pressure built up in closed vessel (CO₂).

Reaction with water, alcohols, amines.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Humidity

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!
At higher temperatures isocyanate may be released.

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	Acute toxicity estimate (ATE)	> 5.000 mg/kg		Expert judgement
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of ethylbenzene and m- xylene and p-xylene	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4- isocyanatosulphonyltolu- ene 4083-64-1	LD50	2.330 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
dibutyltin dilaurate 77-58-7	LD50	2.071 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	LD50	> 2.200 - 2.500 mg/kg	rabbit	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	Acute toxicity estimate (ATE)	2.201 mg/kg		Expert judgement
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	LD50	> 15.800 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4- isocyanatosulphonyltolue ne 4083-64-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
dibutyltin dilaurate 77-58-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist			Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	mildly irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Reaction mass of ethylbenzene and m- xylene and p-xylene	moderately irritating		rabbit	not specified
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
dibutyltin dilaurate 77-58-7	not corrosive		Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
dibutyltin dilaurate 77-58-7	not irritating		Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	other guideline:
dibutyltin dilaurate 77-58-7	not corrosive		Corrositex Biobarrier Membrane (reconstituted collagen matrix)	OECD Guideline 435 (In Vitro Membrane Barrier Test Method for Skin Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Reaction mass of ethylbenzene and m- xylene and p-xylene	moderately irritating		rabbit	not specified
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
dibutyltin dilaurate 77-58-7	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	sensitising	Respiratory sensitisation	guinea pig	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Reaction mass of ethylbenzene and m- xylene and p-xylene	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
dibutyltin dilaurate 77-58-7	Sensitizing	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative	sister chromatid exchange assay in mammalian cells	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Reaction mass of ethylbenzene and m- xylene and p-xylene	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Reaction mass of ethylbenzene and m- xylene and p-xylene	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Reaction mass of ethylbenzene and m- xylene and p-xylene	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
4,4'-methylenebisphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hexane, 1,6-diisocyanato- , homopolymer, V=7000- 11000 mPas/23 28182-81-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
4- isocyanatosulphonyltolue ne 4083-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
4- isocyanatosulphonyltolue ne 4083-64-1	negative	in vitro mammalian chromosome aberration test	with and without		not specified
dibutyltin dilaurate 77-58-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
dibutyltin dilaurate 77-58-7	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
dibutyltin dilaurate 77-58-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1					
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative			mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	negative			rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	negative	intraperitoneal		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
dibutyltin dilaurate 77-58-7	positive	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Reaction mass of ethylbenzene and m-xylene and p-xylene	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	NOAEL P >= 1.720 mg/kg NOAEL F1 >= 1.720 mg/kg	screening	inhalation	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
4-isocyanatosulphonyltoluene 4083-64-1	NOAEL F1 300 mg/kg	one-generation study	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'- methylenebis[4- isocyanatobenzene] 59675-67-1	NOAEL 0,0002 mg/l	inhalation: aerosol	2 years 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	NOAEL 5.000 mg/kg	oral: gavage	13 weeks daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Reaction mass of ethylbenzene and m- xylene and p-xylene	NOAEL 250 mg/kg	oral: gavage	103 w 5 d/w	rat	other guideline:
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	0,34 mm ² /s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	LC50	> 1.000 mg/l	96 h	not specified	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	LL50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	NOEC	> 1,3 mg/l	56 d	Oncorhynchus mykiss	other guideline:
4,4'-methylenediphenyl diisocyanate 101-68-8	LL50	> 100 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2	LC50	> 100 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
4-isocyanatosulphonyltoluene 4083-64-1	LC50	> 45 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
dibutyltin dilaurate 77-58-7	LC50	3,1 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene] 59675-67-1	EC50	> 1.000 mg/l	48 h	not specified	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	EL50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene		> 1 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
dibutyltin dilaurate 77-58-7	EC50	0,463 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	NOELR	> 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	NOEC	1,17 mg/l	7 d	Ceriodaphnia dubia	other guideline:
4,4'-methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Oxirane, methyl-, polymer with oxirane, ether with 1,2,3- propanetriol (3:1), polymer with 1,1'-methylenebis[4- isocyanatobenzene] 59675-67-1	EC50	> 1.640 mg/l	72 h	not specified	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	NOELR	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	EC50	4,7 mg/l	48 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	NOEC	0,44 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2	EC0	> 100 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC50	30 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC10	23 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
dibutyltin dilaurate 77-58-7	EC50	> 1 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4-isocyanatosulphonyltoluene 4083-64-1	EC 50	2.511 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
dibutyltin dilaurate 77-58-7	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	not readily biodegradable.	aerobic	31,3 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	inherently biodegradable	aerobic	72 %	60 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Reaction mass of ethylbenzene and m-xylene and p-xylene	readily biodegradable	aerobic	94 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2		aerobic	1 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4-isocyanatosulphonyltoluene 4083-64-1	readily biodegradable	aerobic	83 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
dibutyltin dilaurate 77-58-7	not readily biodegradable.	anaerobic	23 %	39 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Reaction mass of ethylbenzene and m-xylene and p-xylene	25,9	56 d		Oncorhynchus mykiss	other guideline:
4,4'- methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
dibutyltin dilaurate 77-58-7	31 - 155			Cyprinus carpio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Reaction mass of ethylbenzene and m-xylene and p-xylene	3,16	20 °C	other guideline:
4,4'-methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4-isocyanatosulphonyltoluene 4083-64-1	0,6	30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
dibutyltin dilaurate 77-58-7	4,44	20,8 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 90622-57-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'-methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hexane, 1,6-diisocyanato-, homopolymer, V=7000-11000 mPas/23 28182-81-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4-isocyanatosulphonyltoluene 4083-64-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
dibutyltin dilaurate 77-58-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Hexachlorobenzene CAS 118-74-1

VOC content (2010/75/EU) 6,1 %

VOC Paints and Varnishes (EU):

Product (sub)category:

This product is not a subject of the Directive 2004/42/EC

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.
 H351 Suspected of causing cancer.
 H360FD May damage fertility. May damage the unborn child.
 H370 Causes damage to organs.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.