

according to UK REACH Regulation

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 482 Spray

UFI:

6N3X-V1HS-A00S-RPUF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax:+ 49 (0) 5281 9829860
e-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	
1.4. Emergency telephone	Giftnotruf Berlin: +49 30 30686 700 (Beratung	in Deutsch und Englisch)

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics butanone; ethyl methyl ketone Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Hydrocarbons, C9, aromatics

Danger

Signal word:

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.



DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 2 of 14

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word:	Danger	
Pictograms:		

Hazard statements

H222-H229-H412

Precautionary statements P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP R			
64742-49-0	Hydrocarbons, C7-C9, n-	alkanes, isoalkanes, cyclics		15 - < 20 %
	920-750-0	649-328-00-1	01-2119473851-33	
	Flam. Liq. 2, STOT SE 3,	Asp. Tox. 1, Aquatic Chronic 2; H2	25 H336 H304 H411	
78-93-3	butanone; ethyl methyl ke	etone		15 - < 20 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, S	STOT SE 3; H225 H319 H336 EUH	066	
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			
106-97-8	n-butane			5 - < 10 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compress			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			1 - < 5 %
	927-241-2	649-328-00-1	01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
64742-95-6	Hydrocarbons, C9, aroma	atics		1 - < 5 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, H411 EUH066			
64742-49-0	Hydrocarbons, C6-C7, n-	alkanes, isoalkanes, cyclics, <5% n	-hexane	1 - < 5 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, H411	STOT SE 3, Asp. Tox. 1, Aquatic C	hronic 2; H225 H315 H336 H304	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	c. Limits, M-factors and ATE	
64742-49-0	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	15 - < 20 %
	inhalation: L0 mg/kg	C50 = >23,3 mg/l (vapours); dermal: LD50 = >2800 mg/kg; oral: LD50 = >5000	
78-93-3	201-159-0	butanone; ethyl methyl ketone	15 - < 20 %
	dermal: LD50 = 6480 mg/kg; oral: LD50 = 2740 mg/kg		
	927-241-2	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	1 - < 5 %
	inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 4951 mg/kg		
64742-95-6	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
	inhalation: L0 mg/kg	C50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	1 - < 5 %
	dermal: LD50	0 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).



DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 4 of 14

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

according to UK REACH Regulation

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 5 of 14

6.2. Environmental precautions

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/vapour/aerosol.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

No further relevant information available.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



DINOL GmbH

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 6 of 14

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Worker DNEL	, long-term	dermal	systemic	773 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	2035 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	699 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	608 mg/m³
64742-95-6	Hydrocarbons, C9, aromatics			
Worker DNEL	, long-term	inhalation	systemic	150 mg/m³
Worker DNEL	, long-term	dermal	systemic	25 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	32 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	11 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	11 mg/kg bw/day

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 7 of 14

Test method

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A short-term Filter material/medium : A1/P1 long-term Filter material/medium : A1/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

Changes in the physical state		
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	-42 °C	
Softening point:	not determined	
Flash point:	< -20 °C	DIN 53213
Flammability Solid/liquid:	not determined	
Gas:	not determined	
Explosive properties not determined		
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	11,5 vol. %	
Auto-ignition temperature:	> 200 °C	
Self-ignition temperature		
Solid:	not determined	
Gas:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / dynamic:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	not applicable	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure: (at 20 °C)	8300 hPa	
Density (at 20 °C):	0,82 g/cm³	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not applicable	



DINITROL 482 Spray				
Revision date: 28.04.2022	Product code: 21707	Page 8 of 14		
9.2. Other information				
Information with regard to physical I	nazard classes			
Sustaining combustion:	No data available			
Oxidizing properties not determined				
Other safety characteristics				
Solvent content:	65,1 %			
Solid content:	35,2 %			
Further Information				
No information available.				

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 9 of 14

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64742-49-0	Hydrocarbons, C7-C9, n	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	oral	LD50 >50 mg/kg	000	Rat			
	dermal	LD50 >28 mg/kg	300	Rabbit			
	inhalation (4 h) vapour	LC50 >23 mg/l	3,3	Rat			
78-93-3	butanone; ethyl methyl k	butanone; ethyl methyl ketone					
	oral	LD50 274 mg/kg	40	Rat			
	dermal	LD50 648 mg/kg	30	Rabbit			
	Hydrocarbons, C7, n-alk	anes, isoalkanes,	cyclics				
	oral	LD50 495 mg/kg	51	Rat			
	dermal	LD50 > 5 mg/kg	000	Rat			
	inhalation (4 h) vapour	LC50 495	51 mg/l	Rat			
64742-95-6	Hydrocarbons, C9, aromatics						
	oral	LD50 349 mg/kg	92	Rat			
	dermal	LD50 >3 ⁻ mg/kg	160	Rabbit			
	inhalation (4 h) vapour	LC50 >6 ⁻ mg/l	193	Rat			
64742-49-0	742-49-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			-			
	oral	LD50 >50 mg/kg	000	4			
	dermal	LD50 >50 mg/kg	000	7			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; butanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.



DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 10 of 14

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics							
	Acute fish toxicity	LL50 mg/l	>13,4	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute crustacea toxicity	EL50	3 mg/l		Daphnia magna (Big water flea)			
64742-95-6	Hydrocarbons, C9, aromatics							
	Acute fish toxicity	LC50	9,2 mg/l		Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50	2,9 mg/l		Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50	3,2 mg/l		Daphnia magna (Big water flea)			

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-93-3	butanone; ethyl methyl ketone	0,29
74-98-6	propane	2,36

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of Wastes Code - residues/unused products



DINITROL 482 Spray

Revision date: 28.04.2022

Product code: 21707

Page 11 of 14

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1950 AEROSOLS 2 - 2.1
Classification code: Special Provisions: Limited quantity: Excepted quantity: Transport category: Tunnel restriction code:	5F 190 327 344 625 1 L E0 2 D
Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1950 AEROSOLS 2 - 2.1
Classification code: Special Provisions: Limited quantity: Excepted quantity:	5F 190 327 344 625 1 L E0
Marine transport (IMDG) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1950 AEROSOLS 2.1 - 2.1



according to UK REACH Regulation

DINITROL 482 Spray Revision date: 28.04.2022 Product code: 21707 Page 12 of 14				
Marine pollutant:	no			
Special Provisions:	63, 190, 277, 327, 3	44. 381. 959		
Limited quantity:	1000 mL	.,,		
Excepted quantity:	E0			
EmS:	F-D, S-U			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	UN 1950			
14.2. UN proper shipping name:	AEROSOLS, FLAM	MABLE		
14.3. Transport hazard class(es):	2.1			
14.4. Packing group:	-			
Hazard label:	2.1			
	2			
Special Provisions:	A145 A167 A802			
Limited quantity Passenger:	30 kg G			
Passenger LQ: Excepted quantity:	Y203 E0			
IATA-packing instructions - Passenger:	LU	203		
IATA-max. quantity - Passenger:		75 kg		
IATA-packing instructions - Cargo:		203		
IATA-max. quantity - Cargo:		150 kg		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
Warning : gas				
Other applicable information				
SW1 Protected from sources of heat.				
SW22 For AEROSOLS with a maximu	m capacity of 1			
litre: Category A. For AEROSOLS with				
above 1 litre: Category B. For WASTE				
SG69 For AEROSOLS with a maximum	n capacity of 1			
litre: Segregation as for class 9. Stow "sena	rated from" class			
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.				
For AEROSOLS with a capacity above 1 litre:				
Segregation as for the appropriate subdivision of class				
2.				
For WASTE AEROSOLS:				
Segregation as for the appropriate sub	division of class			
2. Category C, Clear of living quarters.	2. Category C. Clear of living guarters			
SECTION 15: Regulatory information				

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

 Restrictions on use (REACH, annex XVII):

 Entry 29, Entry 40, Entry 75

 2004/42/EC (VOC):

 63,87 %

 524,4 g/l



	DINITROL 482 Spray		
Revision date: 28.04.2022	Product code: 21707	Page 13 of 14	
Information according to 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS		
Additional information Observe in addition any national regulations! Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work			
National regulatory information			
Employment restrictions:	Observe restrictions to employment for juveniles a work protection guideline' (94/33/EC). Observe er under the Maternity Protection Directive (92/85/El nursing mothers.	mployment restrictions	
Water hazard class (D):	2 - obviously hazardous to water		

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,11.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Page 14 of 14



Safety Data Sheet

according to UK REACH Regulation

DINITROL 482 Spray Product code: 21707

Revision date: 28.04.2022

H412 EUH066 Harmful to aquatic life with long lasting effects.

66 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)