Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS\_HU

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant

1.3 Details of the	supplier	of the	safety	data
sheet			•	

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

# 1.4 Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654), or contact your local emergency telephone number at 06 80 20 11 99, 06 1 476 6464

#### **Product Information**

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

<b>Valvoline</b>	Page: 2
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H412 Harmful to aquatic life with long lasting

effects.

Supplemental Hazard

Statements

: EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

P410 + P412

Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in

accordance with local regulation.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### Additional advice

No information available.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### **Hazardous components**

•			
Chemical name	CAS-No.	Classification	Concentration (%)
	EC-No.	(REGULATION (EC)	
	Registration number	No 1272/2008)	
Hydrocarbons, C10-	918-481-9	Asp. Tox.1; H304	>= 40,00 - < 50,00
C13, n-alkanes,	01-2119457273-39-xxxx		
isoalkanes, cyclics, <			
2% aromatics			
Pentane	109-66-0	Flam. Liq.1; H224	>= 15,00 - < 20,00

<b>Valvoline</b>	Page: 3
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

	203-692-4 01-2119459286-30-xxxx	STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	
Substances with a workp	place exposure limit :		
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 5,00 - < 10,00

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Repeated exposure may cause skin dryness or cracking.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

<b>Valvoline</b>	Page: 4
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

#### 5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

#### 6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling

: Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Container may be opened only under exhaust ventilation

hood.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. No smoking.

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m3	2006/15/EC
		TWA	2.950 mg/m3	HU OEL
		STEL	11.800 mg/m3	HU OEL
Butane	106-97-8	TWA	2.350 mg/m3	HU OEL
		STEL	9.400 mg/m3	HU OEL

# 8.2 Exposure controls

### **Engineering measures**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

## Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : transparent

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

8 %(V)

Lower explosion limit / Lower :

flammability limit

0,6 %(V)

Vapour pressure : 573 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0,71 g/cm3 (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : > 200 °C

<b>Valvoline</b>	Page: 8
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

## 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Alkali metals Amines

Oxidizing agents strong bases

strong reducing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Information on likely routes of : Inhalation

exposure

Skin contact
Eye Contact
Ingestion

## **Acute toxicity**

Not classified based on available information.

### **Components:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LD50 (Rat): > 5.000 mg/m3

Exposure time: 8 h

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): >= 3.160 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

**Components:** 

**PENTANE NORMAL:** 

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

**Components:** 

**BUTANE NORMAL:** 

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l

Exposure time: 2 h

LC50 (Rat): > 50000 ppm Exposure time: 2 h Test atmosphere: gas

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

#### **Product:**

Result: Repeated exposure may cause skin dryness or cracking.

# **Components:**

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

#### **PENTANE NORMAL:**

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### **Product:**

Remarks: Unlikely to cause eye irritation or injury.

## **Components:**

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result: No eye irritation

#### PENTANE NORMAL:

Result: Slight, transient irritation

## Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

#### **Components:**

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment: Did not cause sensitisation on laboratory animals.

#### Germ cell mutagenicity

Not classified based on available information.

### **Components:**

## Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Genotoxicity in vitro : Test Type: in vitro assay

Result: negative

#### **BUTANE NORMAL:**

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

<b>Valvoline</b>	Page: 11
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Result: negative

## Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### **Components:**

#### **PENTANE NORMAL:**

Assessment: May cause drowsiness or dizziness.

## STOT - repeated exposure

Not classified based on available information.

## Repeated dose toxicity

### **Components:**

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Species: Rat

NOAEL: >= 1.000 mg/l Application Route: Oral

Method: OECD Test Guideline 422

### **Aspiration toxicity**

Not classified based on available information.

## Components:

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

### **PENTANE NORMAL:**

May be fatal if swallowed and enters airways.

#### **Further information**

#### **Product:**

Remarks: No data available

## **SECTION 12: Ecological information**

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

### 12.1 Toxicity

### **Components:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mg/l

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Pentane

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,7

mg/l

Exposure time: 72 h

Butane

Toxicity to fish : Remarks: No toxicity at the limit of solubility

QSAR

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100

mg/l

Exposure time: 48 h Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l

Exposure time: 96 h Remarks: QSAR

### 12.2 Persistence and degradability

### **Components:**

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradability : Inoculum: activated sludge

Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Pentane

Biodegradability : Result: Readily biodegradable.

Biodegradation: 87 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Butane

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

## 12.3 Bioaccumulative potential

#### **Components:**

Pentane

Partition coefficient: n-

octanol/water

: log Pow: 3,39

Butane

Partition coefficient: n-

octanol/water

: log Pow: 2,89

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

#### **Product:**

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

# **SECTION 13: Disposal considerations**

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

# **SECTION 14: Transport information**

### 14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

## 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

### 14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

## 14.4 Packing group

#### **ADN**

Packing group : Not assigned by regulation

Classification Code : 5F

Valvoline	Page: 15
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Labels : 2.1

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable gas

#### 14.5 Environmental hazards

ADN

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Valvoline	Page: 16
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable

pollutants

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH - Restrictions on the manufacture, placing on : Not applicable

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High : Not applicable

Concern for Authorisation (Article 57).

Regulation (EC) No 649/2012 of the European : Not applicable

Parliament and the Council concerning the export and

import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

major addident nazaras involving	dangerous substances.	Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : 2000 XXV. Law on chemical safety

44/2000. (XII 27) Ministry of health dangerous substances and

: Not applicable

preparations dangerous for certain procedures and

arrangements for activities

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the

protection of young people at work.

Valvoline	Page: 17
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

### The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory

KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA Not On TSCA Inventory

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### 15.2 Chemical safety assessment

No data available

#### **SECTION 16: Other information**

#### **Further information**

Revision Date: 16.11.2018

#### **Full text of H-Statements**

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

**H280** Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

**H336** May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

<b>Valvoline</b>	Page: 18
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

**CSA**: Chemical Safety Assessment

Valvoline	Page: 19
SAFETY DATA SHEET	Revision Date: 16.11.2018
	Print Date: 25.10.2022
	SDS Number: 000000274797
No data.	Version: 1.1
887053	

CSR : Chemical Safety Report DNEL : Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class