

Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_HU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

Product code : 887066

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cleaner.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654), or contact your local emergency telephone number at

+36 80 201 199

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

UFI : 57E3-XU52-TT4E-W7JY

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated

area.

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC)	Concentration (%)			
	Registration number	No 1272/2008)	00.00			
Hydrocarbons, C6-C7,	921-024-6	Flam. Liq.2; H225	>= 80,00 - < 90,00			
n-alkanes, iso-alkanes,	01-2119475514-35-xxxx	Skin Irrit.2; H315				
cyclenes, <5% nhexane		STOT SE3; H336				
		Asp. Tox.1; H304				
		Aquatic Chronic2;				
		H411				
propan-2-ol	67-63-0	Flam. Liq.2; H225	>= 15,00 - < 20,00			
	200-661-7	Eye Irrit.2; H319				
	01-2119457558-25-xxxx	STOT SE3; H336				
Substances with a workplace exposure limit :						
Carbon dioxide	124-38-9	Press. GasLiquefied	>= 1,00 - < 2,50			
	907-631-9	gas; H280	,			

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

> be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

> Remove all sources of ignition. Use personal protective equipment.

Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

: Prevent product from entering drains. **Environmental precautions**

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Container may be opened only under exhaust ventilation

hood.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday. When

using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be

carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane		CEIL (Mist)	5 mg/m3 Mist	HU OEL
		CEIL (Mist)	5 mg/m3 Mist	HU OEL
propan-2-ol	67-63-0	TWA	500 mg/m3	HU OEL
		STEL	2.000 mg/m3	HU OEL
Carbon dioxide	124-38-9	TWA	5.000 ppm 9.000 mg/m3	2006/15/EC
		TWA	9.000 mg/m3	HU OEL
		STEL	72.000 mg/m3	HU OEL

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Valvoline, TM

SAFETY DATA SHEET

Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear.

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : clear

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

12 %(V)

Lower explosion limit / Lower :

flammability limit

0,6 %(V)

Vapour pressure : 85 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Density : 0,72 g/cm3 (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Aldehydes



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

alkalis Amines Ethylene oxide halogens isocyanates

Strong oxidizing agents

Do not use with aluminum equipment at temperatures above

49C or 120 degrees F.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.800 - 3.100 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Acute inhalation toxicity : LC50 (Rat): 16000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Result: Irritating to skin.

ISOPROPANOL:

Result: Slight, transient irritation

CARBON DIOXIDE:

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Result: Slight, transient irritation

ISOPROPANOL:

Result: Irritating to eyes.

CARBON DIOXIDE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects.,



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Solvents may degrease the skin.

Components:

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 11,4 mg/l

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia hyalina (water flea)): 3 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 10 -

30 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC: 0,17 mg/l

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: static test Test substance: WAF

Method: OECD Test Guideline 211

propan-2-ol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450

Exposure time: 96 h Test Type: flow-through test



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Toxicity to daphnia and other

: LC50 (Daphnia magna (Water flea)): > 10.000 mg/l

aquatic invertebrates

Exposure time: 24 h
Test Type: static test

12.2 Persistence and degradability

Components:

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% nhexane

Biodegradability : Inoculum: activated sludge

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

propan-2-ol

Partition coefficient: n-

octanol/water

: log Pow: 0,05

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with

long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

rid

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

: Not applicable

pollutants

Not applicable

REACH - List of substances subject to authorisation

Regulation (EC) No 850/2004 on persistent organic

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1

Quantity 2

E2

ENVIRONMENTAL

200 t 500 t



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

HAZARDS

P3b FLAMMABLE AEROSOLS 5.000 t 50.000 t

Other regulations:

2000 XXV. Law on chemical safety

44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

SECTION 16: Other information

Further information

Internal information: 000000274831

Full text of H-Statements

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization



Version: 2.0 Revision Date: 22.04.2020 Print Date: 25/10/2022

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class