		Page: 1
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_HU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Preparation

<p>1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht Netherlands +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person</p> <p>SDS@valvoline.com</p>	<p>1.4 Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654), or contact your local emergency telephone number at 06 80 20 11 99, 06 1 476 6464</p> <p>Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person</p>
--	---

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements

: EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

: P102 Keep out of reach of children.
Prevention:
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
Storage:
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
 P501 Dispose of contents/container in accordance with regional regulations.

Hazardous components which must be listed on the label:

Pentane
 propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Hazardous components


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Pentane	109-66-0 203-692-4 01-2119459286-30-xxxx	Flam. Liq.1; H224 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 20,00 - < 25,00
Hydrocarbons, C10- C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	918-481-9 01-2119457273-39-xxxx	Asp. Tox.1; H304	>= 15,00 - < 25,00
propan-2-ol	67-63-0 200-661-7 01-2119457558-25-xxxx	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 10,00 - < 15,00
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 10,00 - < 15,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing : Product is compatible with standard fire-fighting agents.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

methods

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up
6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Container may be opened only under exhaust ventilation hood.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m ³	2006/15/EC
		TWA	2.950 mg/m ³	HU OEL
		STEL	11.800 mg/m ³	HU OEL
propan-2-ol	67-63-0	TWA	500 mg/m ³	HU OEL
		STEL	2.000 mg/m ³	HU OEL
Butane	106-97-8	TWA	2.350 mg/m ³	HU OEL
		STEL	9.400 mg/m ³	HU OEL


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

8.2 Exposure controls
Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white, translucent

Odour : alcohol-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	8 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Vapour pressure	:	573 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0,66 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 200 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Aldehydes
Alkali metals
alkalis
Amines
Ethylene oxide
halogenated hydrocarbons
halogens
isocyanates
Oxidizing agents
strong bases
strong reducing agents
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information
11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:
PENTANE NORMAL:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Assessment: Not classified as acutely toxic by ingestion under GHS.

Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Components:
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
 Method: OECD Test Guideline 401
 Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LD50 (Rat): > 5.000 mg/m3
 Exposure time: 8 h
 Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): >= 3.160 mg/kg
 Method: OECD Test Guideline 402
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Components:
ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
 Exposure time: 4 h
 Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg


Components:
BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l
 Exposure time: 2 h

LC50 (Rat): > 50000 ppm
 Exposure time: 2 h
 Test atmosphere: gas

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

		Page: 11
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

ISOPROPANOL:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result: No eye irritation

ISOPROPANOL:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

Components:
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Genotoxicity in vitro : Test Type: in vitro assay
Result: negative

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:
PENTANE NORMAL:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity
Components:
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Species: Rat
NOAEL: >= 1.000 mg/l
Application Route: Oral
Method: OECD Test Guideline 422

Aspiration toxicity


Not classified based on available information.

Components:
PENTANE NORMAL:

May be fatal if swallowed and enters airways.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

		Page: 13
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

Pentane

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h |
| Toxicity to algae | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,7 mg/l
Exposure time: 72 h |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | | |
| Toxicity to fish | : | LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201 |


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 00000274792

No data.
887051

Version: 1.0


- propan-2-ol
Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450 mg/l
Exposure time: 96 h
Test Type: flow-through test
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h
Test Type: static test
- Butane
Toxicity to fish : Remarks: No toxicity at the limit of solubility
QSAR
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l
Exposure time: 48 h
Remarks: QSAR
- Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l
Exposure time: 96 h
Remarks: QSAR

12.2 Persistence and degradability
Components:

- Pentane
Biodegradability : Result: Readily biodegradable.
Biodegradation: 87 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
- Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
- Butane
Biodegradability : Result: Readily biodegradable.
Remarks: Information given is based on data obtained from similar substances.

12.3 Bioaccumulative potential
Components:

- Pentane
Partition coefficient: n- : log Pow: 3,39

		Page: 15
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

octanol/water

propan-2-ol
Partition coefficient: n-
octanol/water : log Pow: 0,05

Butane
Partition coefficient: n-
octanol/water : log Pow: 2,89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

No data.
887051

Version: 1.0

ADN : UN 1950**ADR** : UN 1950**RID** : UN 1950**IMDG** : UN 1950**IATA** : UN 1950**14.2 UN proper shipping name****ADN** : AEROSOLS**ADR** : AEROSOLS**RID** : AEROSOLS**IMDG** : AEROSOLS**IATA** : AEROSOLS**14.3 Transport hazard class(es)****ADN** : 2**ADR** : 2**RID** : 2**IMDG** : 2.1**IATA** : 2.1**14.4 Packing group****ADN**

Packing group : Not assigned by regulation

Classification Code : 5F

Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F

Labels : 2.1

Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F

Hazard Identification Number : 23

Labels : 2.1

IMDG


Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo) : 203

		Page: 17
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

aircraft)
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

IATA (Passenger)

Packing instruction : 203
(passenger aircraft)
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable


SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 25.10.2022

SDS Number: 000000274792

Version: 1.0

No data.
887051

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 57). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : 2000 XXV. Law on chemical safety 44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory


KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA Not On TSCA Inventory

		Page: 19
SAFETY DATA SHEET		Revision Date: 17.10.2018
		Print Date: 25.10.2022
		SDS Number: 000000274792
No data. 887051		Version: 1.0

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 17.10.2018

Full text of H-Statements

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

	Page: 20
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 25.10.2022
	SDS Number: 000000274792
No data. 887051	Version: 1.0

FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging
 CSA : Chemical Safety Assessment
 CSR : Chemical Safety Report
 DNEL : Derived No Effect Level.
 EINECS : European Inventory of Existing Commercial Chemical Substances.
 ELINCS : European List of Notified Chemical Substances
 PEC : Predicted Effect Concentration
 PEL : Permissible Exposure Limits
 PNEC : Predicted No Effect Concentration
 R-phrase : Risk phrase
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
 S-phrase: Safety phrase
 WGK : German Water Hazard Class