

Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_HU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

Product code : 887065

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cleaner.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

Product Information

+36 80 201 199

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

1.4 Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654), or

contact your local emergency telephone number at

SDS@valvoline.com

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

UFI : 59F4-GQ59-PT4M-U1HF

Labelling (REGULATION (EC) No 1272/2008)



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in

accordance with local regulation.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
	EC-No.	(REGULATION (EC)	, ,
	Registration number	No 1272/2008)	
propan-2-ol	67-63-0	Flam. Liq.2; H225	>= 15,00 - < 20,00





Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

	200-661-7 01-2119457558-25-xxxx	Eye Irrit.2; H319 STOT SE3; H336	
ammonia, aqueous solution	1336-21-6 215-647-6	Acute Tox.4; H302 Skin Corr.1B; H314 STOT SE3; H335 Aquatic Acute1; H400 Aquatic Chronic2; H411	>= 0,25 - < 0,50
Substances with a work	place exposure limit :		
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 2,50 - < 5,00
1-Methoxypropan-2-ol	107-98-2 203-539-1 01-2119457435-35-xxxx	Flam. Liq.3; H226 STOT SE3; H336	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.



Revision Date: 16.03.2021 Print Date: 25/10/2022 Version: 2.0

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes serious eye irritation.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing : Product is compatible with standard fire-fighting agents.



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

methods

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday. When

using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	TWA	500 mg/m3	HU OEL
		CEIL	1.000 mg/m3	HU OEL
Butane	106-97-8	TWA	2.350 mg/m3	HU OEL
		CEIL	9.400 mg/m3	HU OEL
1-Methoxypropan-2-ol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
		STEL	150 ppm	2000/39/EC



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

		568 mg/m3	
	TWA	375 mg/m3	HU OEL
	CEIL	568 mg/m3	HU OEL

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Particulates type (P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : clear

Odour : ammoniacal

Odour Threshold : No data available



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

12 %(V)

Lower explosion limit / Lower

flammability limit

2 %(V)

Vapour pressure : 8 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0,91 g/cm3 (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : 425 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to air or moisture over prolonged periods.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Do not use with aluminum equipment at temperatures above

49C or 120 degrees F. Strong oxidizing agents

strong bases

salts of strong bases

isocyanates halogens Ethylene oxide

Amines aluminum alkalis Aldehydes Acids

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Components:

AMMONIUM HYDROXIDE ((NH4)(OH)):

Acute oral toxicity : LD50 (Rat): 350 mg/kg

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l

Exposure time: 2 h

LC50 (Rat): > 50000 ppm Exposure time: 2 h Test atmosphere: gas

Components:

1-METHOXY-2-PROPANOL:

Acute oral toxicity : LD50 (Rat): 4.016 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 13.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ISOPROPANOL:

Result: Slight, transient irritation

AMMONIUM HYDROXIDE ((NH4)(OH)):

Result: Corrosive to skin

1-METHOXY-2-PROPANOL:

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ISOPROPANOL:

Result: Irritating to eyes.

AMMONIUM HYDROXIDE ((NH4)(OH)):

Result: Corrosive

1-METHOXY-2-PROPANOL:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

1-METHOXY-2-PROPANOL:

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

BUTANE NORMAL:



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

1-METHOXY-2-PROPANOL:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Product:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Components:

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

AMMONIUM HYDROXIDE ((NH4)(OH)):

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

1-METHOXY-2-PROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Components:

ISOPROPANOL:



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450

mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 24 h Test Type: static test

ammonia, aqueous solution

Toxicity to fish

: LC50 (Pimephales promelas (fathead minnow)): 8,5 mg/l

Exposure time: 96 h

Butane

Toxicity to fish : Remarks: No toxicity at the limit of solubility

QSAR

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100

mg/l

Exposure time: 48 h Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l

Exposure time: 96 h Remarks: QSAR

1-Methoxypropan-2-ol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

End point: Growth inhibition

Exposure time: 7 d Test Type: static test

12.2 Persistence and degradability

Components:

Butane

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

1-Methoxypropan-2-ol

Biodegradability : Result: Readily biodegradable.

Biodegradation: 96 % Exposure time: 28 d

Method: OECD Test Guideline 301E

12.3 Bioaccumulative potential

Components:

propan-2-ol

Partition coefficient: n-

octanol/water

: log Pow: 0,05

Butane

Partition coefficient: n-

octanol/water

: log Pow: 2,89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic

pollutants

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1

Quantity 2



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

P3a FLAMMABLE AEROSOLS 150 t 500 t

18 Liquefied extremely 50 t 200 t

flammable gases (including LPG) and natural gas

Regulation (EC) No. 648/2004, as amended

: 5 % or over but less than 15 %: Aliphatic hydrocarbons

Other regulations:

2000 XXV. Law on chemical safety

44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : Not On TSCA Inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information: 000000274830

Full text of H-Statements

ruii text of n-Statellie	ents
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Other information

: The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The LINECE administers regional agreements implementing harmonised.

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent . Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class



Version: 2.0 Revision Date: 16.03.2021 Print Date: 25/10/2022