| Valvoline. | Page: 1 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_HU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Preparation

| 1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht Netherlands | 1.4 Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654), or contact your local emergency telephone number at 06 80 20 11 99, 06 1 476 6464 |
|---|---|
| +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person | Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person |
| SDS@valvoline.com | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

| Valvoline | Page: 2 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Hazard pictograms







Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

> Pressurised container: May burst if heated. H229

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects. H411

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

P102 Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

Keep out of reach of children.

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

P410 + P412

Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in

accordance with regional regulations.

Hazardous components which must be listed on the label:

Pentane

propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Valvoline | Page: 3 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

| Chemical name | CAS-No. EC-No. Registration number | Classification (REGULATION (EC) No 1272/2008) | Concentration (%) |
|-------------------------|--|--|--------------------|
| Pentane | 109-66-0 203-692-4 01-2119459286-30-xxxx | Flam. Liq.1; H224 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411 | >= 40,00 - < 50,00 |
| propan-2-ol | 67-63-0 200-661-7 01-2119457558-25-xxxx | Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336 | >= 10,00 - < 15,00 |
| Substances with a workp | place exposure limit : | | |
| Butane | 106-97-8 203-448-7 01-2119474691-32-xxxx | Flam. Gas1; H220 Press. GasLiquefied gas; H280 | >= 15,00 - < 25,00 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

| Valvoline | Page: 4 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes serious eye irritation.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

| Valvoline | Page: 5 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use

| Valvoline. | Page: 6 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday. When

using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------|----------|-------------------------------|--------------------------|------------|
| Pentane | 109-66-0 | TWA | 1.000 ppm 3.000 mg/m3 | 2006/15/EC |
| | | TWA | 2.950 mg/m3 | HU OEL |
| | | STEL | 11.800 mg/m3 | HU OEL |
| Butane | 106-97-8 | TWA | 2.350 mg/m3 | HU OEL |
| | | STEL | 9.400 mg/m3 | HU OEL |
| propan-2-ol | 67-63-0 | TWA | 500 mg/m3 | HU OEL |
| | | STEL | 2.000 mg/m3 | HU OEL |

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse

| Valvoline. | Page: 7 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper : 10,9 %(V)

| Valvoline. | Page: 8 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

flammability limit

Lower explosion limit / Lower : 1,4 %(V)

flammability limit

: 8 hPa (20 °C) Vapour pressure

Relative vapour density No data available

Relative density No data available

Density 0,6 g/cm3 (20 °C)

Solubility(ies)

immiscible Water solubility

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

285 °C Ignition temperature

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic No data available

No data available Oxidizing properties

9.2 Other information

Self-ignition not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

| Valvoline. | Page: 9 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Aldehydes Alkali metals alkalis Amines

Ethylene oxide

halogenated hydrocarbons

halogens isocyanates Oxidizing agents strong bases

strong reducing agents

Do not use with aluminum equipment at temperatures above

49C or 120 degrees F.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

PENTANE NORMAL:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: No adverse effect has been observed in acute

| Valvoline | Page: 10 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

inhalation toxicity tests.

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l

Exposure time: 2 h

LC50 (Rat): > 50000 ppm Exposure time: 2 h Test atmosphere: gas

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

ISOPROPANOL:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

| Valvoline | Page: 11 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

PENTANE NORMAL:

Result: Slight, transient irritation

ISOPROPANOL:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

PENTANE NORMAL:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

PENTANE NORMAL:

May be fatal if swallowed and enters airways.

Further information

Product:

| Valvoline. | Page: 12 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

Pentane

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,7

mg/l

Exposure time: 72 h

propan-2-ol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450

mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 24 h Test Type: static test

Butane

Toxicity to fish : Remarks: No toxicity at the limit of solubility

QSAR

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100

mg/l

Exposure time: 48 h Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l

Exposure time: 96 h Remarks: QSAR

| Valvoline | Page: 13 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

12.2 Persistence and degradability

Components:

Pentane

Biodegradability : Result: Readily biodegradable.

Biodegradation: 87 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Butane

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

12.3 Bioaccumulative potential

Components:

Pentane

Partition coefficient: n-

octanol/water

: log Pow: 3,39

propan-2-ol

Partition coefficient: n-

octanol/water

: log Pow: 0,05

Butane

Partition coefficient: n-

octanol/water

: log Pow: 2,89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

| Valvoline | Page: 14 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F

| Valvoline | Page: 15 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Labels : 2.1

ADR

Packing group Not assigned by regulation

Classification Code 5F 2.1 Labels Tunnel restriction code (D)

RID

Packing group Not assigned by regulation

Classification Code 5F Hazard Identification Number : 23 Labels 2.1

IMDG

Packing group Not assigned by regulation

Labels **EmS Code** F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Y203

Packing instruction (LQ) Not assigned by regulation Packing group

Flammable gas Labels

IATA (Passenger)

Packing instruction 203

(passenger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable gas

14.5 Environmental hazards

Environmentally hazardous no

ADR

Environmentally hazardous : no

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

| Valvoline | Page: 16 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH - Restrictions on the manufacture, placing on : Not applicable

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High : Not applicable

Concern for Authorisation (Article 57).

Regulation (EC) No 649/2012 of the European : Not applicable

Parliament and the Council concerning the export and

import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

| major acoident nazaras involvin | g dangerods substances. | Quantity 1 | Quantity 2 |
|---------------------------------|---|------------|------------|
| P3a | FLAMMABLE AEROSOLS | 150 t | 500 t |
| E2 | ENVIRONMENTAL HAZARDS | 200 t | 500 t |
| 18 | Liquefied extremely flammable gases (including LPG) and natural gas | 50 t | 200 t |

Other regulations : 2000 XXV. Law on chemical safety

44/2000. (XII 27) Ministry of health dangerous substances and

preparations dangerous for certain procedures and

arrangements for activities

Young people under 18 years old are not allowed to work with

| Valvoline | Page: 17 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory

KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA Not On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 17.10.2018

Full text of H-Statements

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate

| Valvoline. | Page: 18 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

| Valvoline. | Page: 19 |
|-------------------|---------------------------|
| SAFETY DATA SHEET | Revision Date: 17.10.2018 |
| | Print Date: 25.10.2022 |
| | SDS Number: 000000274751 |
| No data. | Version: 1.0 |
| 887045 | |

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class