



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_HU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : No data available

Product code : 862067

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654), or
contact your local emergency telephone number at
+36 80 201 199

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 01-2119487077-29-xxxx	Asp. Tox.1; H304	>= 5,00 - < 10,00
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 2,50 - < 5,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Substances with a workplace exposure limit :			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	72623-87-1 276-738-4 01-2119474889-13-xxxx		>= 70,00 - < 80,00
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7 01-2119484627-25-xxxx		>= 5,00 - < 10,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Nitrogen oxides (NO_x)
carbon dioxide and carbon monoxide



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	CEIL (Mist)	5 mg/m3 Mist	HU OEL
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	CEIL (Mist)	5 mg/m3 Mist	HU OEL
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	CEIL (Mist)	5 mg/m3 Mist	HU OEL
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	CEIL (Mist)	5 mg/m3 Mist	HU OEL

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

into eyes.

Hand protection

Remarks : Nitrile rubber butyl-rubber

Skin and body protection : Wear as appropriate:
Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -36 °C

Boiling point/boiling range : not determined

Flash point : 248 °C
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0,853 g/cm ³ (15,6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	< 6.600 mPa.s (-25 °C)
Viscosity, kinematic	:	ca. 95 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
		No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: No mortality observed at this dose.
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l
Exposure time: 4 h



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Test atmosphere: **dust/mist**
Assessment: **Not classified as acutely toxic by inhalation under GHS.**
Remarks: **No mortality observed at this dose.**

Acute dermal toxicity : **LD50 (Rabbit): > 5.000 mg/kg**
Remarks: **No mortality observed at this dose.**

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : **LD50 (Rat): > 15 g/kg**
Acute dermal toxicity : **LD50 (Rabbit): > 5 g/kg**

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: **Slight, transient irritation**

HEAVY PARAFFINIC DISTILLATE:

Result: **Slight, transient irritation**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: **Rabbit**
Result: **Mild skin irritation**
Remarks: **Information given is based on data obtained from similar substances.**

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species: **Rabbit**
Result: **No skin irritation**

HEAVY PARAFFINIC DISTILLATE:

Result: **Slight, transient irritation**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: **Slight, transient irritation**
Remarks: **Expected based on components.**

Remarks: **Unlikely to cause eye irritation or injury.**



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species: Rabbit

Result: No eye irritation

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

HEAVY PARAFFINIC DISTILLATE:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

No aspiration toxicity classification

HEAVY PARAFFINIC DISTILLATE:

No aspiration toxicity classification

Further information

Product:



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment
Short-term (acute) aquatic
hazard

: Not classified based on available information.

Long-term (chronic) aquatic
hazard

: Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : **LL50 (Fish): > 100 mg/l**
Exposure time: **96 h**

Toxicity to daphnia and other
aquatic invertebrates : **EL50 (Aquatic invertebrates): > 10.000 mg/l**
Exposure time: **48 h**

Toxicity to algae : **EL50 (Algae, algal mat (Algae)): > 100 mg/l**
Exposure time: **72 h**

Toxicity to fish (Chronic
toxicity) : **NOEC: 10 mg/l**
Species: **Fish**

Toxicity to daphnia and other
aquatic invertebrates
(Chronic toxicity) : **NOEC: 10 mg/l**
Species: **Aquatic invertebrates**

bis(nonylphenyl)amine

Toxicity to fish : **LC50 (Danio rerio (zebra fish)): > 100 mg/l**
Exposure time: **96 h**
Test Type: **static test**
Remarks: **Information given is based on data obtained from similar substances.**

Toxicity to daphnia and other
aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): > 100 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Toxicity to algae : **EC50 (Pseudokirchneriella subcapitata (algae))**: 600 mg/l
 End point: **Growth inhibition**
 Exposure time: **72 h**
 Test Type: **static test**

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Toxicity to fish : **LL50 (Pimephales promelas (fathead minnow))**: > 100 mg/l
 Exposure time: **96 h**
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 203**
 Remarks: **No toxicity at the limit of solubility**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea))**: > 10.000 mg/l
 Exposure time: **48 h**
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 202**

Toxicity to algae : **NOEL (Pseudokirchneriella subcapitata (green algae))**: >= 100 mg/l
 End point: **Growth inhibition**
 Exposure time: **72 h**
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 201**

Toxicity to fish (Chronic toxicity) : **NOELR: Calculated >= 1.000 mg/l**
 Exposure time: **14 d**
 Species: **Oncorhynchus mykiss (rainbow trout)**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEL: 10 mg/l**
 Exposure time: **21 d**
 Species: **Daphnia (water flea)**
 Test substance: **WAF**
 Method: **OECD Test Guideline 211**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Toxicity to fish : **LL50 (Fish)**: > 100 mg/l
 Exposure time: **96 h**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Aquatic invertebrates)**: > 10.000 mg/l
 Exposure time: **48 h**

Toxicity to algae : **EL50 (Algae, algal mat (Algae))**: > 100 mg/l
 Exposure time: **72 h**

Toxicity to fish (Chronic) : **NOEC: 10 mg/l**



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

toxicity) Species: **Fish**
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEC: 10 mg/l**
Species: **Aquatic invertebrates**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : **Not classified based on available information.**
Long-term (chronic) aquatic hazard : **Not classified based on available information.**

12.2 Persistence and degradability

Components:

bis(nonylphenyl)amine

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **2 - 4 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

12.3 Bioaccumulative potential

Components:

bis(nonylphenyl)amine

Partition coefficient: n-octanol/water : **log Pow: > 7,5**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Partition coefficient: n-octanol/water : **log Pow: Expected > 7**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
DISTILLATES (PETROLEUM),
HYDROTREATED HEAVY
PARAFFINIC (Number on list 28)

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Other regulations:

44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities
2000 XXV. Law on chemical safety

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

AICS	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	Not On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000211820

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

Valvoline's Environmental Health and Safety Department
(+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands



SAFETY DATA SHEET

Version: 5.0

Revision Date: 01.07.2020

Print Date: 25/10/2022

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class