according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 1/(17)

#### **SECTION 1** Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier: A.Z. Meisterteile Motorenöl MT-5D 10W-40
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: semi-synthetic diesel motor oil Uses advised against: application other than the above.
- 1.3 Details of the supplier of the safety data sheet:

Trader identification: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com Technical information: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

Responsible for SDS: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

1.4 Emergency telephone number

Emergency telephone (on workdays: 07-15<sup>20</sup> h (CET)): +36 1 270 8700 Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.) Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary). +36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad) National Health Toxicological Information Service:

### SECTION 2 Hazards identification

2.1	Classification of the substance or mixture							
	Hazard Class and Category:	Hazard stat	ement:					
	Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.					

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



## Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017 Page: 2/(17)

2.2	Label elements					
	Product identification: Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40					
	Hazardous components: -					
	GHS Pictogram:not requiredSignal word:not required					
	Hazard statement: H412 Harmful to aquatic life with long lasting effects.					
	Supplemental hazard information:EUH208Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.					
	Precautionary statements – General: -					
	Precautionary statements – Prevention:P273Avoid release to the environment.					
	Precautionary statements – Response: -					
	Precautionary statements – Storage: -					
	Precautionary statements – Disposal: <b>P501</b> Dispose of contents/container in accordance with national regulation.					
	Other liabilities for labelling: Tactile warning of danger: Not required. Transport classification: see section 14.					
2.3	Other hazards The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006, at a concentration of 0.1% or more. The product contains an endocrine disrupting ingredient: Phenol, dodecyl-, branched (CAS: 121158-58-5) Endocrine disrupting properties (Article 57(f) - human health); Endocrine disrupting properties (Article 57(f) - environment).					

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 3/(17)

#### SECTION 3 Composition/information on ingredients

#### 3.2 Mixtures

Chemical description:

Mixture of refined mineral base oils and synthetic oil containing additives.

Component(s) / Hazardous component(s):

Name	EC number	CAS	Hazard classes and	Hazard	Conc. $0/(m/m)$
Distillates (petroleum),	265-169-7	number 64742-65-0	cat.	statements	%(m/m) max.70
solvent-dewaxed heavy paraffinic*	205-109-7	04742-05-0	(Note L)	-	max.70
REACH Registr. Nr.: 01-2119471299-27					
Distillates (petroleum), hydrotreated heavy paraffinic REACH Registr. Nr.: 01-2119484627-25	265-157-1	64742-54-7	Asp. Tox. 1 (Note L)	H304	max.20
Distillates (petroleum), hydrotreated heavy paraffinic* REACH Registr. Nr.: 01-2119484627-25	265-157-1	64742-54-7	- (Note L)	-	max.20
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based REACH Registr. Nr.: 01-2119474889-13	276-738-4	72623-87-1	Asp. Tox. 1 (Note L)	H304	max.20
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based* REACH Registr. Nr.: 01-2119474878-16	276-737-9	72623-86-0	(Note L)	-	max.20
Distillates (petroleum), solvent-dewaxed light paraffinic REACH Registr. Nr.: 01-2119480132-48	265-159-2	64742-56-9	Asp. Tox. 1 (Note L)	H304	max.15
Highly refined mineral oil (C15 - C50)* REACH Registr. Nr.: no data	-	mixture	(Note L)	-	max.6.0

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3

Latest revision: 17. 11. 2022

Date of issue: 10. 10. 2017

Page: 4/(17)

Name	EC	CAS	Hazard classes and	Hazard	Conc.
ivanie	number	number	cat.	statements	%(m/m)
Phosphorodithioic acid, mixed O,O-bis(1,3- dimethylbutyl and iso-Pr) esters, zinc salts** REACH Registr. Nr.:	283-392-8	84605-29-8	Skin Irrit. 2 Eye Dam. 1 Aquatic Chronic 2	H315 H318 H411	max.1.3
01-2119493626-26 Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased REACH Registr. Nr.: 01-2119524004-56	701-251-5	_	Aquatic Chronic 4	H413	max.1.3
Zinc dialkyl dithiophosphate** REACH Registr. Nr.: 01-2119657973-23	272-238-5	68784-31-6	Eye Dam. 1 Aquatic Chronic 2	H318 H411	max 1.1
Calcium long chain alkaryl sulfonate*** REACH Registr. Nr.: no data	polymer	722503-68-6	Skin Sens. 1B Aquatic Chronic 4	H317 H413	max.1.1
Bis(nonylphenyl)amine REACH Registr. Nr.: 01-2119488911-28	253-249-4	36878-20-3	Aquatic Chronic 4	H413	max.1.1
Phenol, dodecyl-, branched REACH Registr. Nr.: 01-2119513207-49	310-154-3	121158-58-5	Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H314 H318 H360F H400 (M=10) H410 (M=10)	max.0.17
Phenol, (tetrapropenyl) derivatives REACH Registr. Nr.: no data	616-100-8	74499-35-7	Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H314 H318 H360F H400 (M=10) H410 (M=10)	max.0.04

\*: with exposure limit

\*\* Specific concentration limit: Skin Irrit. 2; : 6.25 %  $\leq$  C  $\leq$  100 %; Eye Irrit. 2; : 10 % < C  $\leq$  12.5 %; Eye Dam. 1; : 12.5 % < C  $\leq$  100 %

\*\*\*Specific concentration limit: Skin Sens. 1. H317: C>1,3%

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017 Page:

Page: 5/(17)

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

#### **SECTION 4** First aid measures

4.1	Description o	f first aid measures
	General infor	
	Inhalation:	Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.
	Skin contact:	Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.
	Eye contact:	Flush eyes with plenty of water for 10-15 minutes. In case of persistent irritation, get medical attention.
	Ingestion:	If swallowed, give water. Do not induce vomiting. Get medical attention.
	Protection of	first-aid person: No data available.
4.2	May cause Prolonged	nt symptoms and effects, both acute and delayed an allergic reaction. and/or repeated contact may cause irritation on skin or in eyes depending on sensitivity.

4.3 Indication of any immediate medical attention and special treatment needed Not required.

#### **SECTION 5** Fire-fighting measures

- Fire hazards: Combustible.
- 5.1 Extinguishing media
   Suitable extinguishing media: Foam, carbon dioxide, dry chemical powder, water fog (trained personnel only).

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 6/(17)

Unsuitable extinguishing media: Full water jet.

- 5.2 Special hazards arising from the substance or mixture Hazardous combustion products: On burning, carbon dioxide, carbon monoxide, sulphur oxides, phosphor oxides, various hydrocarbons and soot can be formed.
- 5.3 Advice for fire-fighters
  - Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated firefighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

#### SECTION 6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Personal precautions: see Section 8.
- 6.2 Environmental precautions: Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.
- 6.3 Methods and material for containment and cleaning up
  - On soil: All kind of ignition sources should be removed. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.
  - On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections Personal precautions: see section 8. Waste treatment methods: see section 13.

#### **SECTION 7** Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids. Keep away from radiant heat and open flame.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



Page: 7/(17)

### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists. Wash hands before breaks and at end of work. Take off contaminated clothing and wash it before reuse. When using do not eat, drink or smoke. Avoid splashing the product. Handling temperature: no data

- 7.2 Conditions for safe storage, including any incompatibilities
   Storage facilities must comply with regulations for storing of flammable liquids.
   Store in dry, well-ventilated place in original, closed containers.
   Keep away from radiant heat, open flame and strong oxidizing agents.
   Storage temperature: max. 40°C
- 7.3 Specific end use(s) Semi-synthetic diesel motor oil

#### SECTION 8 Exposure controls / personal protection

8.1 Control parameters:

*Mineral oil mist:* TWA: **5 mg/m<sup>3</sup>**; STEL: 10 mg/m<sup>3</sup>, for oil mist, vapour excluded (ACGIH). Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Engineering control measures: Not required.

Personal protection:

- (a) Eye/face protection
  (b) Skin protection
  (i) Hand protection
  (ii) Hand protection
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
  (iii) Other
  (iii) Protective goggles, if splashes may occur (EN 166).
- (c) Respiratory protection Under normal conditions not required. In case of exceeded exposure-limits respiratory protection with particle-filter is recommended.

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



# Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of

Date of issue: 10. 10. 2017

Page: 8/(17)

	Environmental exposure controls: Do not discharge into drains/surface waters/groundwater	
EC	TION 9 Physical and chemical properties	
.1	Information on basic physical and chemical properties	
	a) Physical state:	liquid
	b) Colour:	brown, clear
	c) Odour:	characteristic
	d) Melting point/freezing point (Pour point) (ISO 3016):	typ36°C
	e) Boiling point or initial boiling point and boiling range	
	(DIN 51356):	not available
	f) Flammability:	combustible
	g) Lower and upper explosion limit:	not explosive
	h) Flash point (COC) (EN ISO 2592):	typ. 230°C
	i) Auto-ignition temperature:	not available
	j) Decomposition temperature:	not available
	k) pH:	not applicable
	<ol> <li>Kinematic viscosity (EN ISO 3104)</li> </ol>	
	at 40°C:	typ. 78.6 mm <sup>2</sup> /s
	at 100°C:	typ. 11.7 mm <sup>2</sup> /s
	m) Solubility	
	Solubility in water:	practically insoluble in water
	Solubility in other solvents:	not available
	n) Partition coefficient n-octanol/water (log value):	not available
	o) Vapour pressure at 20°C:	negligible
	p) Density and/or relative density at 15°C (EN ISO	
	12185):	0.860-0.880 g/cm <sup>3</sup>
	q) Relative vapour density:	not available
	r) Particle characteristics:	not available
9.2	Other information	
	no data available	

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



Page: 9/(17)

### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

#### SECTION 10 Stability and reactivity

10.1 Reactivity:	Dangerous reactivity not known.
10.2 Chemical stability:	No decomposition if stored and handled properly.
10.3 Possibility of hazardous reactions:	Not known.
10.4 Conditions to avoid:	Direct heat or ignition sources.
10.5 Incompatible materials:	Strong oxidizing agents.
10.6 Hazardous decomposition products:	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

#### SECTION 11 Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Based on available data, the classification criteria are not met

Oral:	$LD_{50}$ (rat)						
		> 2000 mg/kg	_				
Dermal:	LD <sub>50</sub> (rabbit)	>2000 mg/kg	(based on components)				
Inhalation:	no data						
Components:							
Distillates (petroleum	ı), hydrotreated heavy p	araffinic (CAS: 64742 -	54-7)				
Oral:	$LD_{50}$ (rat)						
Dermal:	LD <sub>50</sub> (rabbit)	>2000 mg/kg	(OECD 402)				
Inhalation:	$LC_{50}$ (rat)	$> 5000 \ mg/m^3$	(OECD 403)				
Lubricating oils (petr	oleum), C20-50, hydroti	reated neutral oil-based	l (CAS: 72623-87-1)				
Oral:	$LD_{50}$ (rat)	> 5000 mg/kg					
Dermal:	LD <sub>50</sub> (rabbit)	>2000 mg/kg					
Inhalation:	$LC_{50}$ (rat)	>5,53 mg/L					
Lubricating oils (petr	oleum), C20-50, hydrot	reated neutral oil-based	l (CAS: 72623-86-0)				
Oral:	$LD_{50}$ (rat)	> 5000 mg/kg					
Dermal:	LD <sub>50</sub> (rabbit)						
Inhalation:	$LC_{50}$ (rat)	$> 5000 \text{ mg/m}^3$	(dust, mist)				
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)							
Oral:	$LD_{50}$ (rat)	> 5000 mg/kg					
Dermal:	LD <sub>50</sub> (rabbit)	>5000 mg/kg					
Inhalation:	$LC_{50}$ (rat)	>5,00  mg/L(4  h)					

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



Page: 10/(17)

### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)						9)	
	Oral: LD <sub>50</sub> (rat			> 5000	mg/kg	(lite	rature data)	
	Dermal:	LD <sub>50</sub> (rab	bit)	> 2000	mg/kg	(lite	rature data)	
	Inhalation:	$LC_{50}$ (rat)	)	> 5.53	mg/L/4 h	(lite	rature data)	
	Phenol, dodecyl-, sulf	urized, car	bonates, calc	ium salts,	overbased (	EC: 70	1-251-5)	
	Oral:	$LD_{50}$ (rat		> 5000			,	
	Dermal:		bit)					
	Inhalation:	$LC_{50}$ (rat)	,		mg/L/1 h			
	Phenol, (tetrapropeny	l) derivativ	es (CAS: 744	(199-35-7	:			
	Oral:	LD <sub>50</sub> (rat			mg/kg	(OF	ECD 401)	
	Dermal:	, ,	) bit)	15 000			ECD 402)	
	Derman.	LD 50 (140	,01()	15 000	IIIg/ Kg	(01	200 +02)	
	Skin corrosion/irritati	on:	Based on av	ailable da	ata, the class	ificatio	n criteria are not met.	
	Serious eye damage/in	rritation:					n criteria are not met.	
	Respiratory or skin se				,			
	Germ cell mutagenici							
	Carcinogenicity:	•)•	Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.					
	Reproductive toxicity	·•						
	STOT-single exposure:		Based on available data, the classification criteria are not met.					
	STOT-repeated exposure:		Based on available data, the classification criteria are not met.					
	Aspiration hazard:	suic.	Based on available data, the classification criteria are not met.					
	Aspiration nazard.		Dased on av			meanor	il chiena are not met.	
11.2	Information on other	hazards						
	The product contains	an endocri	ne disrupting	g ingredie	nt: Phenol, c	lodecy	l-, branched (CAS:	
	121158-58-5) Endocr					•		
	,	1		<sup>×</sup>			,	
ana		1. 0 .						
SEC	TION 12 Ecologica	linformati	on					
12.1	Toxicity		Harr	nful to ac	luatic life wi	th long	lasting effects.	
	Components:							
	Distillates (petroleum	), hydrotre	ated heavy p	araffinic (	CAS: 64742	-54-7)		
	Fish:				>1000	mg/L	96 h (OECD 203)	
	Daphnia:				>100	mg/L	48 h (OECD 202)	
	Algae:				>100		72 h (OECD 201)	
	In brighting ails (r - t-		0 50 km du = 4	and a day	itual oil har	d (CAR	. 77672 07 1	
	Lubricating oils (petro	neum), C2	•				: /2023-0/-1)	
	Fish:		$LC_{50}$	)	>100	mg/L		

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 11/(17)

Algae:	NOEC	$\geq 100$	mg/L	72 h
Distillates (petroleum), solvent-dew	axed heavy paraffini	ic (CAS: 64	4742-65	5-0)
Fish:	LL/EL/IL <sub>50</sub>	>100	mg/L	
Crustacea:	LL/EL/IL <sub>50</sub>	>100	mg/L	
Crustacea:	LL/EL/IL <sub>50</sub>	>100	mg/L	
Microorganisms:	LC/EC/IC <sub>50</sub>	>100	mg/L	
Fish:	NOEC/NOEL	>100	mg/L	
Crustacea:	NOEC/NOEL	>1 - ≤10	mg/L	
Distillates (petroleum), solvent-dew	axed light paraffinic	(CAS: 64)	742-56-	9)
Fishes:	$LC_{50}$	>100	-	
Other aquatic organisms:	EC <sub>50</sub>	>100	mg/L	
Algae:	$ErC_{50}$	>100	mg/L	
Crustacea:	NOEC	>1	mg/L	
Zinc alkyl dithiophosphate (CAS: 68	3784-31-6)			
Fish (Oncorhynchus mykiss):	$LC_{50}$	4,5	mg/L	96 h
Fish (Mutton-headed carp):	$LC_{50}$	46	mg/L	96 h
Fish (Oncorhynchus mykiss):	NOEC	1,8	mg/L	96 h
Daphnia:	$EC_{50}$	23	mg/L	48 h
Daphnia:	$EC_{50}$		mg/L	21 days
Daphnia:	NOEC	10	mg/L	48 h
Daphnia:	NOEC	0,4	mg/L	21 days
Green algae:	$EC_{50}$	21	mg/L	72 h
Green algae:	NOEC	10	mg/L	72 h
Phenol, dodecyl-, branched (CAS: 1	,			
Fish (Fat-headed carp):	$LC_{50}$	40	mg/L	96 h
Daphnia:	EC <sub>50</sub>	0.037	mg/L	48 h
Shrimp (Mysidopsis Bahia):	$EC_{50}$	>0.58	mg/L	96 h
Daphnia:	$EC_{50}$	0.0079	mg/L	21 days
Daphnia:	NOEC	0.0037	mg/L	21 days
Algae:	EC <sub>50</sub>	0.36	mg/L	72 h
Microorganisms				
(activated sludge):	$EC_{50}$	>1000	mg/L	0.1 day

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



## Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 12/(17)

Phosphorodithioic acid, mixed O,O-bis 84605-29-8)	s(1,3-	dimethylb	outyl and iso-	Pr) este	rs, zinc salts (CAS:	
Fishes (Oncorhynchus mykiss):	LC	-	15	mg/L	96 h	
Fishes (Mutton-headed carp):	LC			mg/L	96 h	
Fishes (Oncorhynchus mykiss):		)EC		mg/L	96 h	
Daphnia:	EC			mg/L	48 h	
Daphnia:	EC			mg/L	21 days	
Daphnia:		)EC		mg/L	48 h	
Daphnia:		DEC		mg/L	21 days	
Green algae:	EC			mg/L	72 h	
Green algae:		)EC		mg/L mg/L	72 h	
Phenol, (tetrapropenyl) derivatives (Ca	4 <i>S:</i> 74	4499-35-2	7)			
Fishes (Fat-headed carp):	LC			mg/L	96 h	
Daphnia:	EC		0.037		48 h	
Shrimp (Mysidopsis Bahia):	EC		> 0.58	0	96 h	
Daphnia:	EC		0.0079		21 days	
Daphnia:		DEC	0.0037		21 days	
Algae:	EC			mg/L	72 h	
Microorganisms (activated sludge):			>1000	-	0,1 day	
Phenol, dodecyl-, sulfurized, carbonate	es, ca	lcium salt	s, overbased	(EC: 70	)1-251-5)	
Fish (Pimephales promelas):	LL		> 1000		96 h	
Mikroorganisms:	EL		> 10000		3 h	
Daphnia magna:	EL		> 1000	U	48 h	
Algae				U		
(Pseudokirchneriella subcapitata):	EL	50	> 500	mg/L	96 h	
12.2 Persistence and degradability						
Biodegradability:		Hydroca	arbons are inl	nerently	degradable.	
Zinc alkyl dithiophosphate (CAS: 6878 31-6)	54 -	1.5% (28 days, OECD TG 301B)				
Phenol, dodecyl-, branched (CAS: 121	·		o duy 5, 010	01050	(1 <b>D</b> )	
58-5)			8 days, OECl	D TG 30	01 B)	
<b>A</b>	Phosphorodithioic acid, mixed O,O-bis(1,3-					
· ·	dimethylbutyl and iso-Pr) esters, zinc salts					
(CAS: 84605-29-8)		1.5% (28 days, OECD TG 301B)				
Phenol, (tetrapropenyl) derivatives (CA 74499-35-7)	4 <i>S:</i>	25.04 (29	Anna OECI	ר ד <u>ר</u> 20	1 <b>D</b> )	
(4499-33-/)		23 % (28	8 days, OECl	01030	( <b>u</b> 1)	

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017 Page: 13/(17)

12.3 Bioaccumulative potential	No data available.
12.4 Mobility in soil Mobility in water:	Absorbs in soil. Floats on water.
12.5 Results of PBT and vPvB asso	essment Does not contain PBT and vPvB substances.
12.6 Endocrine disrupting properti	The product contains an endocrine disrupting ingredient: Phenol, dodecyl-, branched (CAS: 121158-58-5). Endocrine disrupting properties (Article 57(f) - environment).
<ul> <li>12.7 Other adverse effects Heavy metal content: PCT, PCB and other chlorina hydrocarbons: Environmental effects: Water hazard class (German)</li> </ul>	None.

#### SECTION 13 Disposal considerations

13.1 Waste treatment methods
Product disposal:
Wastes of the product or used oil should be treated as hazardous waste.
Waste Identification Code: 13 02 05\*
Mineral-based non-chlorinated engine, gear and lubricating oils.
Waste Identification Code: 13 02 06\*
Synthetic engine, gear and lubricating oils.
Disposal must be in compliance with national and local regulations.
Recommended waste treatment method: incineration
Packaging disposal:
Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.
Waste Identification Code: 15 01 10\*
Packaging containing residues of or contaminated by dangerous substances.
Disposal must be in compliance with national and local regulations.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 14/(17)

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

#### SECTION 14 Transport information

	Land transport: Road/ Railway	ADR/RID:	Not classified.		
14.1	UN number or ID number:		Not classified.		
14.2	UN proper shipping name:		Not classified.		
14.3	4.3 Transport hazard class(es):		Not classified.		
14.4	.4 Packing group:		Not classified.		
14.5	4.5 Environmental hazards:		Not classified.		
14.6	4.6 Special precautions for user:		Not classified.		
	Waterways:				
	Inland waterways/ Sea transport	ADN/IMDG:	Not apply to the product.		
	Air transport: ICAO / IATA:		Not apply to the product.		

#### SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008. Seveso category: not classified.
- 15.2 Chemical safety assessment. not available

#### **SECTION 16** Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use.

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017 Page: 15/(17)

The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Aquatic Chronic 3 H412 calculated

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304 H314 H315 H317 H318	May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Asp. Tox. 1 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1B Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 4	Aspiration hazard Category 1 Skin corrosion/irritation Category 1C Skin corrosion/irritation Category 2 Respiratory/skin sensitization Category 1 Serious eye damage/eye irritation Category 1 Reproductive toxicity Category 1B Hazardous to the aquatic environment, Acute Category 1 Hazardous to the aquatic environment, Chronic Category 1 Hazardous to the aquatic environment, Chronic Category 2 Hazardous to the aquatic environment, Chronic Category 4

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017

Page: 16/(17)

Legend:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	BiologicalOxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Carcinogenic, Mutagenic or toxic to Reproduction
DMEL	Chemical Oxygen Demand
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ecx	Effective Concentration x%
ErC50	EC50 in terms of reduction of growth rate
Edx	Effective Dose x%
EC	European Community
EC number	European Community number
ELINCS	European List of Notified Chemical Substances
ES	ExposureScenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	LethalConcentrationx%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts/million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International carriage of Dangerous Goods by Rail

according to regulation (EC) No  $1907/2006\,(REACH)\,and\,1272/2008/EC$ 



### Trade name: A.Z. Meisterteile Motorenöl MT-5D 10W-40

Version: 3 Latest revision: 17. 11. 2022 Date of issue: 10. 10. 2017 Pag

Page: 17/(17)

SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

Revision Indicators:					
Section	Subject of change	Date	Version		
3 11	Composition/information on ingredients Toxicological information	31.01.2020	2		
12	Ecological information				
1-16	Revision modification according to 2020/878/EU Full revision due to composition change	17.11.2022	3		