

A.Z. Meisterteile Motorenöl MT-7 5W-30

synthetic motor oil

Product benefits

- long oil drain interval, low operating cost
- high performance, long engine life
- fully synthetic, fuel saving engine oil
- excellent cold flow property, easy cold start
- extra low volatility, low oil consumption
- stay-in-grade shear stability and excellent wear protection

Applications

A.Z. Meisterteile Motorenöl MT-7 5W-30 energy saving engine oil exceeds the requirements of the most important automobile associations and engine manufacturers.

A.Z. Meisterteile Motorenöl MT-7 5W-30 fulfils the diesel engines' requirements of General Motors (Opel, Chevrolet and Daewoo).

A.Z. Meisterteile Motorenöl MT-7 5W-30 is a state-of-the-art engine oil developed for the most advanced gasoline or diesel passenger cars and light commercial vehicles with naturally aspirated or turbocharged operation.

Specifications and approvals

ACEA A3/B4
API SL/CF
VW 502 00/505 00
GM-LL-B-025

Product description

A.Z. Meisterteile Motorenöl MT-7 5W-30 synthetic motor oil manufactured from synthetic base oils and complex additive system (detergent/dispersant, antioxidant, antiwear, anticorrosive and antifoam agents, flow improver).

Due to its low evaporation characteristics the product reduces oil consumption, and consequently exhaust emission of harmful chemicals.

Its oxidation stability specific to synthetic oils ensures the original properties to remain unchanged and prevents deposit and sludge formation even at permanently high engine operating temperatures.

Thanks to its excellent cold viscosity property provides immediate lubrication and full engine protection even at extremely low temperatures.

Typical properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,852
Kinematic viscosity at 40°C [mm ² /s]	70,87
Kinematic viscosity at 100 °C [mm ² /s]	12,00
Pour point [°C]	-36
Flash point (Cleveland) [°C]	220
Base number (BN) [mg KOH/g]	10,2

The characteristics in table are typical values of the product and do not constitute a specification.

A.Z. Meisterteile Motorenöl MT-7 5W-30
synthetic motor oil

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

Shelf life in the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C