

A.Z. Meisterteile Getriebeöl ATF VI

Product benefits

- extended fluid life
- improved oxidation and thermal stability
- flows well for cold start-up
- outstanding resistance against sludge and deposit formation
- maintains lubricity
- improved anti-wear protection which contributes to extended transmission life

Applications

A.Z. Meisterteile Getriebeöl ATF VI is a super premium quality, multipurpose automatic transmission fluid that can be used in many types of transmissions.

A.Z. Meisterteile Getriebeöl ATF VI exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles transmissions or power steering service where a DEXRON®-VI, DEXRON®-IIIH, III, IIE and II type ATF is specified.

Fulfils Toyota's World Standard (WS) newest generation specification of ATF market.

Specifications and approvals

GM Dexron-VI
Toyota WS
Nissan Matic-W
Mitsubishi ATF J3
BMW 83 22 0 142 516
Ford Mercon LV
Honda DW-1
Hyundai NWS-9638
Hyundai/Kia SP-IV
Nissan Matic-S
SAAB 93 165 147

Product description

A.Z. Meisterteile Getriebeöl ATF VI automatic transmission fluid is formulated from synthetic base oils using advanced complex additive system (antioxidant, antwear, anticorrosion, antifoam and flow- and friction modifying) suitable for high quality requirements of Japanese and Korean passenger cars.

Due to its special formulation it has excellent flow and friction properties required for a trouble-free operation in a wide temperature range.

Its extremely low cold viscosity ensures the proper operation of the hydraulic control elements even under very cold conditions.

Typical properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,847
Kinematic viscosity at 40°C [mm ² /s]	29,5
Kinematic viscosity at 100 °C [mm ² /s]	6,0
Viscosity index	155
Pour point [°C]	-49
Flash point (Cleveland) [°C]	210

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

Shelf life in the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C