according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2 Previous Issue / Date of last revision (manufacturers): -/ 17. 02. 2022

ision Date of issue: 18. 03. 2021 Page: 1/(15) Date revision: 31. 10. 2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier **A.Z. Meisterteile Motor Starter Spray** UFI: 5SXV-XHGF-R42U-RVFR
- 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: motor starter spray. Maintenance product for residential and professional use.
 Uses advised against: application other than the above

Uses advised against: application other than the above.

1.3. Details of the supplier of the safety data sheet:

Distributor Details: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

It is related to the use of the product technical information: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

Responsible for SDS: UNIX Autó és Alkatrészkereskedelmi Kft. H-1139 Budapest, Frangepán u. 55-57. Tel.: +36 1 270 8700 Fax: +36 1 270 8799 E-mail: cs@unixauto.com

1.4. Emergency telephone number

Emergency telephone (07-15²⁰ h): +36 1 270 8700 (CET) on workdays Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián út 2-6.) Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary). +36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

SECTION 2: Hazards identification

2.1.	Classification of the substance or mixture						
	Hazard Class and Category:	Hazard statement:					
	Aerosol 1	H222	Extremely flammable aerosol				
	Aerosol 1	H229	Pressurized container: may burst if heated.				
	Eye Irrit. 2	H319	Causes serious eye irritation.				
	STOT SE 3	H336	May cause drowsiness or dizziness.				

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): -/ 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 2/(15)
Page: 2/(15)

2.2.	Label elements	
	Product identification	tion: Trade name: A.Z. Meisterteile Motor Starter Spray
	Hazardous compo	onents: Diethyl ether; Butanone; Kerosine (petroleum), hydrodesulfurized
	GHS Pictogram:	
	Signal word:	Danger
	Hazard statement H222 H229 H319 H336	Extremely flammable aerosol Pressurized container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
	Supplemental haz EUH019 EUH066	ard information: May form explosive peroxides. Repeated exposure may cause skin dryness or cracking.
	Precautionary star P101 P102	tements – General: If medical advice is needed, have product container or label at hand. Keep out of reach of children.
	Precautionary stat P210	tements – Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261 P273	Avoid breathing spray. Avoid release to the environment.
	P280	Wear protective gloves, protective clothing, eye protection/face protection.
	Precautionary star P304 + P340 P305 + P351 + P338 P337 + P313	tements – Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention.
	Precautionary star P403 + P233 P405 P410 + P412	tements – Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.
	Precautionary star P501	tements – Disposal: Dispose of contents/container in accordance with national regulation.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 3/(15)

Other liabilities for labelling:

Tactile warning of danger and child-resistant fastening:Not required.Transport classification: see section 14.

2.3. Other hazards

Product can form flammable/explosive gas/vapour/air mixtures. Results of PBT and vPvB assessment: Does not contain PBT and vPvB substances. Endocrine disrupting properties: no data.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical description:

Mixtures of the following substances and non-hazardous substances with propellant gas.

Component(s) / Hazardous component(s):

Name	EC	CAS	Hazard classes and	Hazard	Conc.
<u></u>	number	number	cat.	statements	%(m/m)
Diethyl ether	200-467-2	60-29-7	Flam. Liq. 1	H224	<40
REACH Registr. Nr.:			Acute Tox. 4	H302	
01-2119535785-29			STOT SE 3	H336	
				EUH019	
				EUH036	
Butanone	201-159-0	78-93-3	Flam. Liq. 2	H225	<35
REACH Registr. Nr.:			Eye Irrit. 2	H319	
01-2119457290-43			STOT SE 3	H336	
				EUH066	
Kerosine (petroleum),	265-184-9	64742-81-0	Flam. Liq. 3	H226	<5.0
hydrodesulfurized			Asp. Tox. 1	H304	
REACH Registr. Nr.:			Skin Irrit. 2	H315	
01-2119462828-25			STOT SE 3	H336	
			Aquatic Chronic 2	H411	
Hydrocarbons, C10-C13, n-	918-481-9	-	Asp. Tox. 1	H304	<5.0
alkanes, isoalkanes, cyclics,			(Note J)	EUH066	
<2% aromatics			× ,		
REACH Registr. Nr.:					
01-2119457273-39					
Isopropyl alcohol	200-661-7	67-63-0	Flam. Liq. 2	H225	<1.0
REACH Registr. Nr.:	····		Eye Irrit. 2.	H319	
01-2119457558-25			STOT SE 3	H336	

L.L. Meisterteile®

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2 Previous Issue / Date of last revision (manufacturers): - / 17. 02. 2022 Date of issue: 18. 03. 2021 Page: 4/(15) Date revision: 31. 10. 2023

Name	EC	CAS	Hazard classes and	Hazard	Conc.
Ivallie	number	number	cat.	statements	%(m/m)
Propellant gas:					
Propane	200-827-9	74-98-6	Flam. Gas 1	H220	-
REACH Registr. Nr.:			Press. Gas	H280	
01-2119486944-21					
Butane*	203-448-7	106-97-8	Flam. Gas 1	H220	-
REACH Registr. Nr.:			Press. Gas	H280	
01-2119474691-32					
Isobutane*	200-857-2	75-28-5	Flam. Gas. 1	H220	-
REACH Registr. Nr.:			Press. Gas.	H280	
01-2119485395-27					

*1,3-butadiene (CAS: 106-99-0) <0.1%

Note J: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes.

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General informati	on: Never give anything by mouth to an unconscious person, or never				
	induce vomiting.				
Inhalation:	Remove exposed person to fresh air. In case of complaints, get medical				
	advice.				
Skin contact:	Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, contact a doctor.				
Eye contact:	Flush eyes with plenty of water for 10-15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of persistent irritation, contact a doctor.				
Ingestion:	Not possible under normal conditions. When happened, rinse mouth with water. Do not induce vomiting (aspiration hazard). Get medical attention.				
Protection of first-aid person: It may be hazardous to the person providing aid to give mouth-to-					

mouth resuscitation.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2 Previous Issue / Date of last revision (manufacturers): - / 17. 02. 2022

tion Date of issue: 18. 03. 2021 Page: 5/(15) Date revision: 31. 10. 2023

4.2. Most important symptoms and effects, both acute and delayed Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Propellant gas: In high concentrations, it has a suffocating effect, the lack of oxygen has fatal consequences.

4.3. Indication of any immediate medical attention and special treatment needed Symptomatic treatment. Constant monitoring for the first 48 hours is important. Show safety data sheet or label to doctor.

SECTION 5: Fire-fighting measures

5.1. Extinguishing mediaSuitable extinguishing media: Foam, carbon dioxide, dry chemical powder, water spray.

Unsuitable extinguishing media:

Full water jet. They could cause splattering and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

- 5.2. Special hazards arising from the substance or mixture Hazardous combustion products: In case of combustion carbon monoxide, carbon dioxide, peroxides, various hydrocarbons and
- 5.3. Advice for fire-fighters

soot can be formed.

Special protective equipment: According to the existing fire-fighting regulations. Self-contained breathing apparatus.

Further information:

Use water spray just to cool down surfaces exposed to fire. Collect contaminated fire-fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 6/(15)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.
Keep persons not involved in rescue at a distance.
Sufficient ventilation should be provided.
Keep away from sources of ignition – No smoking.
Avoid contact with skin, clothing and eyes, inhalation of gas, vapour, aerosol.
Danger of slipping on leaked out/spilled product.

6.2. Environmental precautions:

Prevent spills from entering into natural water, soil and drains by containing the liquid. All kind of ignition sources should be removed. Do not smoke. Notify relevant authority.

- 6.3. Methods and material for containment and cleaning up Exclude source of ignition. Adequate ventilation required in enclosed areas. Keep away from sources of ignition. Use non-sparking tools. Contain spilled liquid with sand, earth or other neutral material and place in suitable containers for disposal (dangerous waste).
- 6.4. Reference to other sections Personal precautions: see section 8. Waste treatment methods: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Keep general measures applied for normal operations with chemicals and extremely flammable aerosols. Adequate ventilation or local exhaust must be provided. Keep away from sources of ignition - No smoking. Product can form flammable/explosive gas/vapour/air mixtures. Keep container in vertical position avoiding falls and strokes. Use explosion-proof and non-sparking tools. Do not pierce or burn, even after use. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Take measures to prevent electrostatic charges. Avoid contact with skin, clothing and eyes, inhalation of gas, vapour, aerosol. Wash hands before breaks and at end of work. Take off contaminated clothing and wash it before reuse. When using do not eat or drink. Handling temperature: no data.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 7/(15)

7.2. Conditions for safe storage, including any incompatibilities

Keep general measures applied for storage of flammable and explosive materials.
Store in dry, well-ventilated place in original, closed containers.
Keep away from direct sunshine, direct heat or ignition sources, electrostatic charging and strong oxidizing agents, nitrates, halogens.
Keep away from food, drink and feed.
Keep out of reach of children.
Storage temperature: max. 35°C.

7.3. Specific end use(s) Motor starter spray. Maintenance product for residential and professional use.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

		Wor	kplace exp				
Substance	CAS number	long therm exposure limit (8- hr)		short therm exposure limit (15- min.)		Comments	
		mg/m ³	ppm	mg/m ³	ppm		
Diethylether	60-29-7	308	100	616	200	-	
Butanone	78-93-3	600	200	900	300	-	

8.2. Exposure controls

Engineering control measures:

Adequate ventilation.

Personal protection:

(a) Eye/face protection	Where splashing is possible, wear tightly fitting safety glasses (EN 166).
(b) Skin protection	
(i) Hand protection	Protective gloves (EN 374).
	Note: Manufacturer's directions for use and the conditions of application should be observed.
(ii) Other	For regular use, impervious protective clothing should
(c) Respiratory protection	In case of vapor or aerosol formation, a respirator with a suitable filter (A) is required.
(d) Thermal hazards	No data.
Environmental exposure control	ols:

Do not discharge into drains/surface waters/groundwater.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2 Previous Issue / Date of last revision (manufacturers): -/ 17. 02. 2022

Vision Date of issue: 18. 03. 2021 Page: 8/(15) Date revision: 31. 10. 2023

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	a)	Physical state:	aerosol (active ingredient: liquid,
			under pressure)
	b)	Colour:	colorless
	c)	Odour:	characteristic of ether
	d)	Melting point/freezing point:	not available
	e)	Boiling point or initial boiling point and boiling range:	not available
	f)	Flammability:	Extremely flammable aerosol
	g)	Lower and upper explosion limit:	not available
	h)	Flash point:	not available
	i)	Auto-ignition temperature:	not available
	j)	Decomposition temperature:	not available
	k)	pH:	not available
	1)	Kinematic viscosity:	not available
	m)	Solubility	
		Solubility in water:	partly miscible with water
		Solubility in other solvents:	not available
	n)	Partition coefficient n-octanol/water (log value):	not available
	0)	Vapour pressure:	not available
	p)	Density and/or relative density:	not available
	q)	Relative vapour density:	not available
	r)	Particle characteristics:	not available
9.2.	Oth	ner information	
		No data available.	

SECTION 10: Stability and reactivity

10.1. Reactivity	Dangerous reactivity not known.
10.2. Chemical stability	No decomposition if stored and handled properly.
10.3. Possibility of hazardous reactions	Not known.
10.4. Conditions to avoid	High temperature (over 50°C), ignition source, heat source, open flame, spark, direct sunlight, electrostatic charging.
10.5. Incompatible materials	Strong oxidizing agents, nitrates, halogens, strong acids, alkalis.
10.6. Hazardous decomposition products	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 9/(15)

SECTION 11: Toxicological information

11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008							
	Acute toxicity: Based on	available	e data, the cla	ssificatior	n criteria are no	ot met		
	Components: Diethyl ether (CAS: 60-29-7)							
	Oral:	LD50 (r	<i>.</i>		mg/kg			
	Kerosine (petroleum), hydrodesulfurized (CAS: 64742-81-0) (literature data) Oral: LD ₅₀ (rat) > 5000 mg/kg							
	Oral: Dermal:	· · · ·	at) abbit)					
	Inhalation:	LD_{50} (r	· ·		mg/L			
	<i>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (EC: 918-481-9) (literature data)</i>							
	Oral:	LD ₅₀ (r	at)	> 5000	mg/kg			
	Dermal:				> 2000 mg/kg			
	Inhalation: LC ₅₀ (ra		at)	> 5.2	mg/L			
	Izopropil-alkohol (CAS: 67-63-0)							
	Oral:	LD ₅₀ (r		5840	mg/kg	(OECD 401)		
	Dermal: LD_{50} (r		abbit)	13900	mg/kg	(OECD 402)		
	<i>Propane (CAS: 74-98-6)</i>							
	Inhalation:	LC_{50} (ra	at)	1443	mg/L/4 h	(literature data)		
	Butane (CAS: 106-97-8)							
	Inhalation:	LC_{50} (ra	at)	658	mg/L/4 h	(literature data)		
	Isobutane (CAS: 75-28-5)							
	Inhalation:	$LC_{50}(n$	nouse)	974	mg/L/4 h			
	Skin corrosion/irritation: Serious eye damage/irrita	Based on available data, the classification criteria are not met. Causes serious eye irritation.						
	Respiratory or skin sensi			•		cation criteria are not met.		
	Germ cell mutagenicity:					cation criteria are not met.		
	Carcinogenicity:			available data, the classification criteria are not met.				
	Reproductive toxicity:			· · · · · · · · · · · · · · · · · · ·	cation criteria are not met.			
						rowsiness or dizziness.		
	STOT-repeated exposure Aspiration hazard:	:				cation criteria are not met. cation criteria are not met.		
11.2	-	anda		unuore de		canon ontona are not mot.		
11.2.	Information on other haz Endocrine disrupting pro		io data.					

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2	Previous Issue / Date of last revision	Date of issue: 18. 03. 2021	Page: 10/(15)
	(manufacturers): - / 17. 02. 2022	Date revision: 31. 10. 2023	

SECTION 12: Ecological information

12.1. Toxicity No data available for the product. Components: *Kerosine (petroleum), hydrodesulfurized (CAS: 64742-81-0) (literature data)* 1-20 mg/L Fish: LC_{50} Other aquatic organisms: EC50 1-20 mg/L Crustacea: EC_{50} 1-20 mg/L Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cvclics, <2% aromatics (EC: 918-481-9) *(literature data)* Fish: LC 50 1-10 mg/L Other aquatic organisms: EC_{50} 1-10 mg/L 1-10 mg/L Crustacea: EC 50 Isopropyl alcohol (CAS: 67-63-0) 9640 mg/L/96 h Pimephales promelas: LC_{50} Daphnia magna: 10000 mg/L/48 h EC50 Green algae: EC_{50} 1800 mg/L/7 days Lactuca sativa: 2104 mg/kg/72 h IC₅₀ Propane (CAS: 74-98-6) Fish: LC_{50} 49.47 mg/L (literature data) Other aquatic organisms: LC_{50} 27.14 mg/L (literature data) EC_{50} 11.89 mg/L/72 h (literature data) Algae: Butane (CAS: 106-97-8) Fish: LC₅₀ 24.11 mg/L (literature data) (literature data) Other aquatic organisms: LC_{50} 14.22 mg/L 7.71 mg/L/96 h EC_{50} (literature data) Algae: Isobutane (CAS: 75-28-5) Fish: LC_{50} 27.98 mg/L (literature data) Other aquatic organisms: LC_{50} 16.33 mg/L (literature data) Algae: EC₅₀ 8.57 mg/L/96 h (literature data)

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2	Previous Issue / Date of last revision	Date of issue: 18. 03. 2021	Page: 11/(15)
	(manufacturers): - / 17. 02. 2022	Date revision: 31. 10. 2023	

12.2.	Persistence and degradability Biodegradability:	No data available for the product.
	Kerosine (petroleum), hydrodesulfurized (CAS: 64742-81-0): Hydrocarbons, C10-C13, n-alkanes,	inherently degradable (literature data)
	<i>isoalkanes, cyclics, <2% aromatics (EC: 918-481-9):</i>	80% (28 days)
	Isopropyl alcohol (CAS: 67-63-0):	53% (5 days) easily biodegradable
12.3.	Bioaccumulative potential	No data available for the product.
	<i>Kerosine (petroleum), hydrodesulfurized (CAS: 64742-81-0):</i>	Log Kow: >4; potentially bioaccumulative (literature data)
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
	(EC: 918-481-9):	Log Pow: 2.1-6.0 (literature data); Log Kow: >4; potentially bioaccumulative (literature data)
	Isopropyl alcohol (CAS: 67-63-0)	Log Pow <1.0 (bioaccumulation not expected)
12.4.	Mobility in soil	The mineral oil floats on water, adsorbs into the soil particulates and loses its mobility.
	Mobility in water:	No data.
12.5.	Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances.
12.6.	Endocrine disrupting properties	No data.
12.7.	Other adverse effects	
	Environmental effects:	Do not allow to enter drains, watercourses, soil or groundwater.
	Water hazard class (German):	No data.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste. Waste Identification Code: 16 05 04*

Gases in pressure containers (including halons) containing dangerous substances.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 12/(15)
Page: 12/(15)

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

SECTION 14: Transport information

14.2.	UN number or ID number UN proper shipping name Transport hazard class(es)	UN1950 AEROSOLS, flammable 2 (classification code: 5F)
	Packing group	-
14.5.	Environmental hazards	not classified
	Marine pollutant:	no
14.6.	Special precautions for user	- /
	Labels:	2.1
1.4.7	Tunnel restriction code:	2 (D)
14.7.	Maritime transport in bulk according to IMO instruments	not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008. Seveso category: P3.a.

15.2. Chemical safety assessment. not available

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2

Previous Issue / Date of last revision (manufacturers): - / 17. 02. 2022 Date of issue: 18. 03. 2021 Page: 13/(15) Date revision: 31. 10. 2023

SECTION 16: Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)		
Aerosol 1	H222	calculation method (based on flammable components)
Aerosol 1	H229	calculation method (based on flammable components)
Eye Irrit. 2	H319	calculation method
STOT SE 3	H336	calculation method

The full text of each relevant Hazard classes and cat. and H- phrase in Section 3.:

H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Flam. Gas 1	Flammable gas Category 1
Flam. Liq. 1	Flammable liquid Category 1
Flam. Liq. 2	Flammable liquid Category 2
Flam. Liq. 3	Flammable liquid Category 3
Press Gas	Compressed gas
Acute Tox. 4	Acute toxicity Category 4
Asp. Tox. 1	Aspiration hazard Category 1

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: A.Z. Meisterteile Motor Starter Spray

Version: 2Previous Issue / Date of last revision
(manufacturers): - / 17. 02. 2022Date of issue: 18. 03. 2021
Date revision: 31. 10. 2023Page: 14/(15)

Skin Irrit. 2 Eye Irrit. 2 STOT SE 3 Aquatic Chroni	 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Specific target organ toxicity — single exposure Category 3 ic 2 Hazardous to the aquatic environment, Chronic Category 2
Legend:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (1272/2008/EC)
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ecx	Effective Concentration x%
Edx	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC50	EC50 in terms of reduction of growth rate;
ES	Exposure Scenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



A.Z. Meisterteile Motor Starter Spray Trade name:

Version: 2	Previous Issue / Date of last revision	Date of issue: 18. 03. 2021	Page: 15/(15)
	(manufacturers): - / 17. 02. 2022	Date revision: 31. 10. 2023	

REACHRegistration, Evaluation, Authorisation and Restriction of ChemicalsRIDRegulations concerning the International Carriage of Dangerous Goods by RailSVHCSubstance of Very High ConcernUVCBsubstance of unknown or variable composition, complex reaction products or biological materiaVOCVolatile organic compoundsvPvBVery Persistent and very Bio-accumulative			ological materials
Section	Subject of change	Date	Version
1-16	Revision modification according to 2020/878/EU. Full revision due to composition change.	31. 10. 2023	2