Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Product code SDS # Product type Castrol Transmax Manual V 75W-80 469686-DE01 469686 Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

	nd greases in vehicles or machinery-Industrial nd greases in vehicles or machinery-Professional		
Use of the substance/ mixture	Manual transmission fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative.		
.3 Details of the supplier of	f the safety data sheet		
Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam		
	Castrol CEE sp z.o.o, UI. Grzybowska 62, 00 844 Warszawa		
	+48 (0)800 121 4817		
E-mail address	MSDSadvice@bp.com		
.4 Emergency telephone nu	umber		
EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)		
ECTION 2: Hazards	dentification		

 Product definition
 Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Aquatic Chronic 3, H412

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements	
Signal word	No signal word.
Hazard statements	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	P273 - Avoid release to the environment.
Response	Not applicable.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	Not applicable.

Product name	Castrol Transn	nax Manual V 75W-80		Product code	469686-DE01	Page: 1/16
Version 7	Date of issue	8 September 2023	Format	Hungary	Language	ENGLISH
Date of previ	ous issue	5 January 2023.		(Hungary)		

SECTION 2: Hazards identification

Supplemental label elements	Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.		
EU Regulation (EC) No. 1907/	2006 (REACH)		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.		
Special packaging requireme	<u>nts</u>		
Containers to be fitted with child-resistant fastenings	Not applicable.		
Tactile warning of danger	Not applicable.		
2.3 Other hazards			
Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do not result in classification	Experimental data on one or more of the components has been used to determine all or part of the hazard classification of this product. Defatting to the skin.		

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition

```
Mixture
```

Synthetic base stock. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
1-Decene, homopolymer, hydrogenated	REACH #: 01-2119486452-34 EC: 500-183-1 CAS: 68037-01-4	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 EC: 500-183-1 CAS: 157707-86-3	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Reaction products of 4-methyl- 2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: 931-384-6 CAS: -	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/ kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1, H317: C ≥ 9.39%	[1]
Distillates (petroleum), solvent- dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1] [2]
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)- alkylamines	REACH #: 01-2119473797-19 EC: 627-034-4 CAS: 1213789-63-9	≤0.3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/ kg M [Acute] = 10 M [Chronic] = 10	[1]
isodecyl methacrylate	REACH #: 01-2119894925-17 EC: 249-978-2 CAS: 29964-84-9 Index: 607-134-00-4	≤0.3	Aquatic Chronic 1, H410 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	STOT SE 3, H335: C ≥ 10% M [Acute] = 1 M [Chronic] = 1	[1]
Product name Castrol Transma	x Manual V 75W-80		Product code 469	686-DE01 Page:	2/16
Version 7 Date of issue	8 September 2023		Format Hungary	Language ENGL	ISH
Date of previous issue	5 January 2023.		(Hungary)		

M [Acute] = 1

M [Chronic] = 1

[1]

SECTION 3: Composition/information on ingredients

REACH #:	≤0.3	Flam. Liq. 3, H226
01-2119457739-21		Asp. Tox. 1, H304
EC: 212-819-2		Aquatic Acute 1, H400
CAS: 872-05-9		Aquatic Chronic 1, H410
	01-2119457739-21 EC: 212-819-2	01-2119457739-21 EC: 212-819-2

See Section 16 for the full text of the H statements declared above.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effect	<u>s</u>
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.Product not classified for sensitisation. Based on data available for this or related materials.
Eye contact	Not classified as an eye irritant. Based on data available for this or related materials.
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.
5.2 Special hazards arising fr	om the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide) metal oxide/oxides

5.3 Advice for firefighters

ſ	Product name	Castrol Transma	ax Manual V 75W-80		Product code	469686-DE01	Page: 3/16
	Version 7	Date of issue	8 September 2023	Format	Hungary	Language	ENGLISH
	Date of previo	ous issue	5 January 2023.		(Hungary)		

SECTION 5: Firefighting measures

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures			
For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.			
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".			
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.			
6.3 Methods and material for c	containment and cleaning up			
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.			
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.			

SECTION 7: Handling and storage

Date of issue 8 September 2023

5 January 2023.

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Version 7

Date of previous issue

Product name Castrol Trans	max Manual V 75W-80	Product code 469686-DE01	Page: 4/16
7.3 Specific end use(s)			
Not suitable	Prolonged exposure to elevated tempera	ure	
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulat from incompatible materials (see Sect container tightly closed and sealed un be carefully resealed and kept upright containers designed for use with this p appropriate containment to avoid envi	ion 10). Keep away from heat and diru til ready for use. Containers that have to prevent leakage. Store and use on product. Do not store in unlabelled cor	ect sunlight. Keep been opened must ly in equipment/
Advice on general occupational hygiene	Eating, drinking and smoking should b stored and processed. Wash thoroug protective equipment before entering information on hygiene measures.	hly after handling. Remove contamina	ated clothing and
Protective measures	Put on appropriate personal protective and clothing. Avoid breathing vapour soil and surface waterways. Keep in t from a compatible material, kept tight containers retain product residue and	or mist. Avoid contact of spilt material he original container or an approved a / closed when not in use. Do not reus	l and runoff with Iternative made
	-		

Format Hungary

(Hungary)

Language ENGLISH

SECTION 7: Handling and storage

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Product/ingredie	nt name	Exposure limit values	
Distillates (petroleum), solvent-		5/2020. (II. 6.) ITM Decree (Hungary). [Oil (mineral)]	
paraffinic		TWA: 5 mg/m ³ 8 hours. Issued/Revised: 2/2020 Form: Mis	+
		be shown in this section, other components may be present in a DELs may not be applicable to the product as a whole and are pr	ny mist,
Recommended monitoring procedures	EN 689 (Workpla chemical agents Standard EN 140 for the assessme (Workplace atmo measurement of	d be made to monitoring standards, such as the following: Europ ce atmospheres - Guidance for the assessment of exposure by for comparison with limit values and measurement strategy) Eur 42 (Workplace atmospheres - Guide for the application and use nt of exposure to chemical and biological agents) European Sta spheres - General requirements for the performance of procedu chemical agents) Reference to national guidance documents for of hazardous substances will also be required.	inhalation to ropean of procedures andard EN 482 res for the
Biological exposure indices			
Product/ingredient No exposure indices known.	name	Exposure indices	
Derived No Effect Level No DNELs/DMELs available.			
Predicted No Effect Concentra No PNECs available	<u>ation</u>		
8.2 Exposure controls			
Appropriate engineering controls	concentrations be All activities invol exposures are ad after other forms Personal protecti kept in good cond Your supplier of p appropriate stand The final choice of	ventilation or other engineering controls to keep the relevant airb elow their respective occupational exposure limits. ving chemicals should be assessed for their risks to health, to er lequately controlled. Personal protective equipment should only of control measures (e.g. engineering controls) have been suital ve equipment should conform to appropriate standards, be suita dition and properly maintained. Dersonal protective equipment should be consulted for advice on lards. For further information contact your national organisation of protective equipment will depend upon a risk assessment. It is ms of personal protective equipment are compatible.	nsure be considered bly evaluated. ble for use, be selection and for standards.
ndividual protection measure	<u>es</u>		
Hygiene measures	smoking and usir	earms and face thoroughly after handling chemical products, bef ng the lavatory and at the end of the working period. Ensure that ty showers are close to the workstation location.	
Respiratory protection	The correct choic conditions of wor should be develo	tient ventilation, wear suitable respiratory equipment. The of respiratory protection depends upon the chemicals being have and use, and the condition of the respiratory equipment. Safety ped for each intended application. Respiratory protection equipment and in consultation with the supplier/manufacturer and with a full nditions.	y procedures nent should
Eye/face protection	Safety glasses w	ith side shields.	
Skin protection			
Hand protection	General Informa	tion:	
	should be develo depends upon the provide protection	work environments and material handling practices vary, safety ped for each intended application. The correct choice of protecti e chemicals being handled, and the conditions of work and use. In for only a limited time before they must be discarded and repla esistant gloves will break down after repeated chemical exposure	ve gloves Most gloves ced (even the
Product name Castrol Transmax	Manual V 75W/ 90	Product code 469686-DE01	Page: 5/16

Product name Castrol Transmax Manual V 75W-80			Product code	469686-L	DE01	Page: 5/16		
Version 7	Date of issue	8 September 2023	Format	Hungary		Language	ENGLISH	
Date of previo	ous issue	5 January 2023.		(Hungary)				

SECTION 8: Exposure controls/personal protection

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves. **Breakthrough time:**

	Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:						
	Continuous contact:						
	Gloves with a minimum breakthroug can be obtained. If suitable gloves are not available t breakthrough times may be accepta replacement regimes are determine	o offer th able as lo	at level of protection, g ng as appropriate glove	loves with sh	orter		
	Short-term / splash protection:						
	Recommended breakthrough times It is recognised that for short-term, t may commonly be used. Therefore, be determined and rigorously follow	ransient appropr	exposures, gloves with				
	Glove Thickness:						
	For general applications, we recom	mend glo	oves with a thickness ty	pically greate	r than 0.35 mm.		
	It should be emphasised that glove resistance to a specific chemical, as on the exact composition of the glov on consideration of the task require Glove thickness may also vary depe glove model. Therefore, the manufa to ensure selection of the most app	s the peri ve materi ments ar ending or acturers'	meation efficiency of th al. Therefore, glove se ad knowledge of breaktion the glove manufacture technical data should a	e glove will b lection should hrough times er, the glove	e dependent d also be based type and the		
	Note: Depending on the activity bein for specific tasks. For example:	ng condu	icted, gloves of varying	thickness ma	ay be required		
	• Thinner gloves (down to 0.1 mm dexterity is needed. However, these would normally be just for single use	gloves a	are only likely to give sh	nort duration			
	• Thicker gloves (up to 3 mm or m as a chemical) risk i.e. where there				anical (as well		
Skin and body	Use of protective clothing is good in Personal protective equipment for the performed and the risks involved ar product. Cotton or polyester/cotton overalls of contamination that will not soak three basis. When the risk of skin exposed risk of splashing) then chemical rest will be required.	he body nd should will only p ough to th ure is hig	should be selected bas I be approved by a spe provide protection again he skin. Overalls should h (e.g. when cleaning u	cialist before nst light supe d be laundere ıp spillages o	handling this rficial ed on a regular r if there is a		
<u>Refer to standards:</u>	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 4 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387	05					
Product name Castrol Transma			Product code 469686		Page: 6/16		
	3 September 2023	Format	Hungary	Language	ENGLISH		
Date of previous issue	5 January 2023.		(Hungary)				

SECTION 8: Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flammability	Not available.
Lower and upper explosion limit	Not available.
Flash point	Open cup: >200°C (>
Auto-ignition temperature	Ingredient name

Open cup: >200°C (>392°F) [Cleveland]

Ingredient name	°C	°F	Method
1-Decene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Not available.			
Not applicable.			
Kinematic: 40 mm²/s (40 cSt) Kinematic: 8.1 mm²/s (8.1 cSt			

Result

Not soluble

Solubility

pH

Partition coefficient n-octanol/ water (log value)

Decomposition temperature

Kinematic viscosity

Vapour pressure

	Vapour Pressu		ire at 20°C Vapou		ur pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
1-Decene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87				
Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87				
diisodecyl azelate	0	0					
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191				

Density and/or Relative density Relative vapour density Particle characteristics Median particle size 9.2 Other information Evaporation rate Explosive properties Oxidising properties Pour point

<1000 kg/m3 (<1 g/cm3) at 15°C

Not available.

Not applicable.

Not available.

Not available.

Not available.

<-60 °C

Media

Not applicable.

water

Product name C	Castrol Transma	ax Manual V 75W-80		Product code	469686-DE01	Page: 7/16
/ersion 7	Date of issue	8 September 2023	Format	Hungary	Language	ENGLISH
Date of previo	us issue	5 January 2023.		(Hungary)		

SECTION 10: Stability	SECTION 10: Stability and reactivity					
10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.					
10.2 Chemical stability	The product is stable.					
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.					
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).					
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.					
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.					

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity estimates

ſ

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Sastrol Transmax Manual V 75W-80 Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus	19676.9 500	N/A N/A	N/A N/A	N/A N/A	N/A N/A
sulphide (P2S5) and propylene oxide (Z)-octadec-9-envlamine	500	N/A	N/A	N/A	N/A

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.Product not classified for sensitisation. Based on data available for this or related materials.
Eye contact	Not classified as an eye irritant. Based on data available for this or related materials.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.
Delayed and immediate effe	ects as well as chronic effects from short and long-term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Potential chronic health eff	ects
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards

Product name	Castrol Transm	ax Manual V 75W-80		Product code	469686-D	E01	Page: 8/16
Version 7	Date of issue	8 September 2023	Format	Hungary		Language	ENGLISH
Date of previo	us issue	5 January 2023.		(Hungary)			

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 **SECTION 11: Toxicological information** 11.2.1 Endocrine disrupting properties Not available. **Remarks - Endocrine** Not available. disruptor - Health 11.2.2 Other information Not available. SECTION 12: Ecological information 12.1 Toxicity Harmful to aquatic life with long lasting effects. **Environmental hazards** Based on data available for this or related materials. 12.2 Persistence and degradability Not expected to be rapidly degradable. **12.3 Bioaccumulative potential** This product is not expected to bioaccumulate through food chains in the environment. 12.4 Mobility in soil Soil/water partition Not available. coefficient (Koc) Mobility Spillages may penetrate the soil causing ground water contamination. 12.5 Results of PBT and vPvB assessment Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII. NI . 4

12.6 Endocrine disrupting properties	Not available.
Remarks - Endocrine disruptor - Environment	Not available.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
12.7 Other adverse effects	No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Hazardous waste	Yes.
<u>European waste catalogue (l</u>	EWC)

Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

rackaging	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
References	Commission 2014/955/EU Directive 2008/98/EC

Product name Castrol Transmax Manual V 75W-80			Product code 469	686-DE01	Page: 9/16	
Version 7	Date of issue 8 September 2023		Format	Hungary	Language	ENGLISH
Date of previ	ous issue	5 January 2023.		(Hungary)		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Not available. 14.6 Special precautions for user

14.7 Maritime transport in bulk according to IMO instruments

Date of previous issue

SECTION 15: Regulatory information

Not available.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation Annex XIV None of the components are listed. Substances of very high concern None of the components are listed. EU Regulation (EC) No. 1907/2006 (REACH) **Annex XVII - Restrictions** Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other regulations REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH. **United States inventory** All components are active or exempted. (TSCA 8b) Australia inventory (AIIC) All components are listed or exempted. **Canada inventory** All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** At least one component is not listed. (PICCS) **Taiwan Chemical** All components are listed or exempted. Substances Inventory (TCSI) Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Product name Castrol Transmax Manual V 75W-80 Product code 469686-DE01 Page: 10/16 Version 7 Date of issue 8 September 2023 **Format Hungary**

(Hungary) 5 January 2023.

Language ENGLISH

SECTION 15: Regulatory information

Not listed.

Persistent	Organic	Pollutants
Not listed.		

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

References	Act No. XXV of 2000 on chemical safety
	Decree No. 25/2000 (IX.30.) EüM of the Ministry of Health on chemical safety at work plus amendments
	Decree No. 44/2000 (XII.27.) EüM of the Ministry of Health on detailed arrangements for certain procedures, activities relating to dangerous substances and dangerous preparations plus amendments
	38/2009 (VII.7) The International Carriage of Dangerous Goods by the European Agreement (ADR) "A" and "B" on the application of national annex plus amendments
15.2 Chemical safety assessment	A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by
	Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by
	Road
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	CSA = Chemical Safety Assessment
	CSR = Chemical Safety Report
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EINECS = European Inventory of Existing Commercial chemical Substances
	ES = Exposure Scenario
	EUH statement = CLP-specific Hazard statement
	EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as
	modified by the Protocol of 1978. ("Marpol" = marine pollution)
	OECD = Organisation for Economic Co-operation and Development
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	RRN = REACH Registration Number
	SADT = Self-Accelerating Decomposition Temperature SVHC = Substances of Very High Concern
	STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
	STOT-SE = Specific Target Organ Toxicity - Single Exposure
	TWA = Time weighted average
	UN = United Nations
	UVCB = Complex hydrocarbon substance
	VOC = Volatile Organic Compound
	vPvB = Very Persistent and Very Bioaccumulative
	Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23,
	64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN
	01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN
	01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN
	01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN
	01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN
	01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8,
	64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 /
Broduct name Costrol Transmo	

Product name Castrol Transmax Manual V 75W-80		Product code	469686-D)E01	Page: 11/16		
Version 7	Date of issue	8 September 2023	Format	Hungary		Language	ENGLISH
Date of previo	ous issue	5 January 2023.		(Hungary)			

SECTION 16: Other information

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classifi	cation	Justification
Aquatic Chronic 3, H412		Expert judgment
Full text of abbreviated H statements	H226 H302 H304 H314 H315 H317 H318 H319 H335 H373 H400 H410 H411	Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye damage. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 3 Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1B STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
<u>History</u>		
Date of issue/ Date of	08/09/2023.	
revision		
revision Date of previous issue	05/01/2023.	

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

ſ	Product name Castrol Transmax Manual V 75W-80			Product code	469686-DE01	Page: 12/16	
	Version 7	Date of issue	8 September 2023	Format	Hungary	Language	ENGLISH
Date of previous issue		ous issue	5 January 2023.		(Hungary)		



Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture	
--	--

	Product definition	Mixture
	Code	469686-DE01
	Product name	Castrol Transmax Manual V 75W-80
	Section 1: Title	
	Short title of the exposure scenario	General use of lubricants and greases in vehicles or machinery - Industrial
	List of use descriptors	Identified use name: General use of lubricants and greases in vehicles or machinery-Industrial Process Category: PROC01, PROC08b, PROC09, PROC02
		Sector of end use: SU03
		Subsequent service life relevant for that use: No.
		Environmental Release Category: ERC04, ERC07
_		Specific Environmental Release Category: ATIEL-ATC SPERC 4.Biv1
	Processes and activities covered by the exposure scenario	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure No exposure scenario is presented because the product is not classified for Human Health Contributing scenarios: Operational conditions and risk management measures

Castrol Transmax Manual V 75W-80	General use of lubricants and greases in vehicles or machinery - Industrial
Technical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Release fraction to wastewater from process (after typical onsite RMMs and before sewage treatment plan)	Not available.
Release fraction to soil from process (after typical onsite RMMs)	0
Release fraction to air (after typical onsite RMMs)	5.00E-05
Other conditions affecting environmental exposure:	Negligible wastewater emissions as process operates without water contact.
Local marine water dilution factor	100
Local freshwater dilution factor	10
Environment factors not influenced by risk management:	
Emission days	300
Frequency and duration of use:	
EU tonnage of risk determining substance per year:	2.63E+3 Tonnes/year
Amounts used:	
Section 2.2: Control of environmental exp Amounts used:	Josure

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant
Organisational measures to prevent/limit release from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	Not available.
Assumed domestic sewage treatment plant flow rate (m3/d)	2.00E+3
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal as product:	Not available.
Conditions and measures related to external treatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste:	External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment		
Exposure assessment (environment):	Used ECETOC TRA model (May 2010 release).	
Exposure estimation and reference to its source - Workers		
Exposure estimation and reference to its s	ource - Workers	

Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	No exposure scenario is presented because the product is not classified for Human Health



Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture	
Product definition	Mixture
Code	469686-DE01
Product name	Castrol Transmax Manual V 75W-80
Section 1: Title	
Short title of the exposure scenario	General use of lubricants and greases in vehicles or machinery - Professional
List of use descriptors	Identified use name: General use of lubricants and greases in vehicles or machinery-Professional
	Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20 Sector of end use: SU22
	Subsequent service life relevant for that use: No.
	Environmental Release Category: ERC09a, ERC09b Specific Environmental Release Category: ATIEL-ATC SPERC 9.Bp.v1
Processes and activities covered by the exposure scenario	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure No exposure scenario is presented because the product is not classified for Human Health Contributing scenarios: Operational conditions and risk management measures

	machinery - Professional 15/16
Castrol Transmax Manual V 75W-80	General use of lubricants and greases in vehicles or
Fechnical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Release fraction to wastewater from proces (after typical onsite RMMs and before sewage treatment plan)	s Not available.
Release fraction to soil from process (after typical onsite RMMs)	1E-03
Release fraction to air (after typical onsite RMMs)	1.00E-04
Other conditions affecting environmental exposure:	Negligible wastewater emissions as process operates without water contact.
Local marine water dilution factor	100
Local freshwater dilution factor	10
Environment factors not influenced by risk management:	
Emission days	365
Frequency and duration of use:	
EU tonnage of risk determining substance per year:	5.39 Tonnes/year
Amounts used:	
Section 2.2: Control of environmental ex	posure

echnical on-site conditions and measures	Prevent discharge of undissolved substance to or recover from onsite
o reduce or limit discharges, air emissions nd releases to soil:	wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant
organisational measures to prevent/limit elease from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
conditions and measures related to sewage reatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	No data available yet
Assumed domestic sewage treatment plant flow rate (m3/d)	2.00E+3
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewate treatment removal as product:	No data available yet r
conditions and measures related to external reatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
conditions and measures related to external ecovery of waste:	External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment		
Exposure assessment (environment):	Used ECETOC TRA model (May 2010 release).	
Exposure estimation and reference to its source - Workers		
Exposure estimation and reference to its s	ource - Workers	

Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	No exposure scenario is presented because the product is not classified for Human Health