

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 1 / 13

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

automatic transmission fluid (ATF) Article number: 29934, 101161, 101162

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

# 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

**Hazard pictograms** 

**Hazard statements** H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling Contains: 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. EUH208 May produce an

allergic reaction.

# 2.3 Other hazards

**Physico-chemical hazards** No particular hazards known.

**Human health dangers** Frequent persistent contact with the skin can cause skin irritation.

**Environmental hazards**Does not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards none

#### **SECTION 3: Composition / Information on ingredients**

# 3.1 Substances

not applicable



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 2 / 13

#### 3.2 Mixtures

#### The product is a mixture.

| Range [%]     | Substance   |
|---------------|---|
| 20 - < 50     | Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based  |
|               | CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX                           |
|               | GHS/CLP: Asp. Tox. 1: H304  |
| 1 - < 5       | Bis(nonylphenyl)amine   |
|               | CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX   |
|               | GHS/CLP: Aquatic Chronic 4: H413  |
| 1 - < 5       | Phenol derivates  |
|               | GHS/CLP: Aquatic Chronic 4: H413  |
| 0,1 -< 1      | 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate  |
|               | CAS: 93882-40-7, EINECS/ELINCS: 299-434-3, Reg-No.: 01-2120735527-50  |
|               | GHS/CLP: Skin Sens. 1: H317 - Eye Irrit. 2: H319 - Aquatic Chronic 2: H411  |
| 0,01 - < 0,25 | Alkyl thiophosphites  |
|               | EINECS/ELINCS: 424-820-7, Reg-No.: 01-0000017126-75-xxxx  |
|               | GHS/CLP: Skin Corr. 1B: H314 - Acute Tox. 4: H312 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400, M-Factor (chronic): 10 |

Comment on component parts

For full text of H-statements and R-phrases: see SECTION 16. Contains less than 3% w/w DMSO-extract (only for mineral oils)

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General information Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Get medical advice.

# 4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.

Treat symptomatically.

Forward this sheet to your doctor.

# **SECTION 5: Fire-fighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

#### 5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO)



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 3 / 13

#### 5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

#### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

# 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

#### 6.3 Methods and material for containment and cleaning up

Take up residues with absorbent material (e.g. sand).

Dispose of absorbed material in accordance within the regulations.

#### Reference to other sections

See SECTION 8+13

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

No special measures necessary if used correctly.

The product is combustible.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container tightly closed. Protect from heat/overheating.

#### Specific end use(s)

See product use, SECTION 1.2



# Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 4 / 13

# SECTION 8: Exposure controls / personal protection

# 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

not relevant

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

#### DNEL

| Substance   |  |  |
|---|--|--|
| Bis(nonylphenyl)amine, CAS: 36878-20-3  |  |  |
| Industrial, dermal, Long-term - systemic effects, 5 mg/kg bw/day                      |  |  |
| general population, dermal, Long-term - systemic effects, 2,5 mg/kg bw/day            |  |  |
| general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day             |  |  |
| Alkyl thiophosphites  |  |  |
| Industrial, inhalative, Long-term - systemic effects, 1,76 mg/m³                      |  |  |
| Industrial, dermal, Long-term - systemic effects, 0,5 mg/kg bw/day                    |  |  |
| general population, inhalative, Long-term - systemic effects, 0,43 mg/m³              |  |  |
| general population, dermal, Long-term - systemic effects, 0,25 mg/kg bw/day           |  |  |
| general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day             |  |  |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1 |  |  |
| Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³                      |  |  |
| Industrial, inhalative, Long-term - local effects, 5.58 mg/m³                         |  |  |
| Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day                    |  |  |
| general population, inhalative, Long-term - local effects, 1.19 mg/m³                 |  |  |
| general population, inhalative, Long-term - systemic effects, 740 μg/kg bw/day        |  |  |
| 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7                 |  |  |
| Industrial, inhalative, Long-term - systemic effects, 3.526 mg/m³ (AF= 75)            |  |  |
| Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/d (AF= 300)              |  |  |
| general population, oral, Long-term - systemic effects, 0.5 mg/kg bw/d (AF= 600)      |  |  |

#### **PNEC**

Substance

| Bis(nonylphenyl)amine, CAS: 36878-20-3  |  |
|---|--|
| freshwater, 412 µg/L  |  |
| seawater, 41.2 µg/L   |  |
| sediment (freshwater), 1 mg/kg sediment dw  |  |
| sediment (seawater), 0.1 mg/kg sediment dw  |  |
| Alkyl thiophosphites  |  |
| freshwater, 900 ng/l  |  |
| seawater, 90 ng/l   |  |
| sewage treatment plants (STP), 54 mg/l  |  |
| sediment (freshwater), 0,073 mg/kg  |  |
| sediment (seawater), 0,007 mg/kg  |  |
| soil, 0,015 mg/kg   |  |
| oral (food), 10 mg/kg   |  |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1 |  |



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 5 / 13

| oral (food), 9.33 mg/kg food  |  |
|---|--|
| 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7 |  |
| freshwater, 0.009 mg/L (AF= 1000)                                     |  |
| seawater, 0.001 mg/L (AF= 10 000)                                     |  |
| sewage treatment plants (STP), 100 mg/L (AF= 10)                      |  |
| sediment (freshwater), 542 229.75 mg/kg dw                            |  |
| sediment (seawater), 54 222.98 mg/kg dw                               |  |
| soil, 259 870.48 mg/kg dw   |  |
| oral (food), 20 mg/kg food (AF=300)                                   |  |

# 8.2 Exposure controls

Additional advice on system design 
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

**Eye protection** If there is a risk of splashing:

safety glasses (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).> 0,4 mm; Neoprene, >480 min (EN 374-1/-2/-3).

Skin protection light protective clothing

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection not applicable

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

#### Page 6 / 13

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state liquid
Form liquid
Color red-brown
Odor characteristic
Odour threshold not relevant
pH-value not applicable
pH-value [1%] not applicable

Boiling point or initial boiling point

and boiling range [°C]

No information available.

Flash point [°C] 212

Flammability No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] No information available.

Density [g/cm³] 0,84 (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water immiscible

Solubility other solvents No information available.

Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity 34 mm<sup>2</sup>/s (40° C)

Relative vapour density

Mo information available.

Melting point [°C]

Auto-ignition temperature [°C]

Decomposition temperature [°C]

Particle characteristics

No information available.

No information available.

#### 9.2 Other information

none

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reactions known if used as directed.

# 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

No dangerous reactions known if used as directed.

#### 10.4 Conditions to avoid

Strong heating.



# Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 7 / 13

# 10.5 Incompatible materials

Oxidizing agent Strong basic compounds Strong acids.

# 10.6 Hazardous decomposition products

No hazardous decomposition products known.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 8 / 13

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute oral toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3

LD50, oral, Rat, 5000 mg/kg bw

Alkyl thiophosphites

LD50, oral, Rat, > 2000 mg/kg

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, oral, Rat, 5000 mg/kg bw

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7

LD50, oral, Rat, > 10 000 mg/kg bw

#### Acute dermal toxicity

Product

ATE-mix, dermal, 202.669 mg/kg bw

Substance

Alkyl thiophosphites

LD50, dermal, Rabbit, > 500 mg/kg

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

# Acute inhalational toxicity

Substance

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

**Skin corrosion/irritation**Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available. May produce an allergic reaction.

Calculation method

Specific target organ toxicity —

Respiratory or skin sensitisation

single exposure

Based on the available information, the classification criteria are not fulfilled.

**Specific target organ toxicity** — Based on the available information, the classification criteria are not fulfilled. **repeated exposure** 

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3

NOEL, oral, Rat, 100 mg/kg bw/day

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 9 / 13

MutagenicityBased on the available information, the classification criteria are not fulfilled.Reproduction toxicityBased on the available information, the classification criteria are not fulfilled.CarcinogenicityBased on the available information, the classification criteria are not fulfilled.Aspiration hazardBased on the available information, the classification criteria are not fulfilled.

**General remarks** 

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

11.2.1 Endocrine disrupting

properties

Contains no ingredients with endocrine-disrupting properties.

**11.2.2 Other information** No information available.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

| Substance   |  |  |
|---|--|--|
| Bis(nonylphenyl)amine, CAS: 36878-20-3  |  |  |
| EC50, (48h), Invertebrates, 100 mg/L  |  |  |
| EL50, (72h), Algae, 100 mg/L  |  |  |
| NOELR, (21d), Invertebrates, 4.45 mg/L  |  |  |
| NOELR, (33d), fish, 10 mg/L   |  |  |
| Alkyl thiophosphites  |  |  |
| EL50, (48h), Daphnia magna, 0,09 mg/l   |  |  |
| EL50, (72h), Selenastrum capricornutum, 0,31 mg/l                                     |  |  |
| LL50, (24h), Oncorhynchus mykiss, 2 mg/l  |  |  |
| LL50, (21d), Daphnia magna, 0,22 mg/l   |  |  |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1 |  |  |
| NOELR, (14d), fish, 1 g/L   |  |  |
| LL50, (4d), Invertebrates, 10 g/L   |  |  |
| LL50, (4d), fish, 100 mg/L  |  |  |
| 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7                 |  |  |
| LC50, (96h), fish, > 100 mg/l (OECD 203)  |  |  |
| EL50, (48h), Daphnia magna, 9,5 mg/l (OECD 202)                                       |  |  |
| EL50, (72h), Algae, > 100 mg/l (OECD 201)   |  |  |

# 12.2 Persistence and degradability

Behaviour in environment not determined

compartments

Behaviour in sewage plant not determined Biological degradability not determined

# 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 10 / 13

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

# 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

#### 12.7 Other adverse effects

Do not discharge product unmonitored into the environment.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

For recycling, consult manufacturer.

Waste no. (recommended) 130205\* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102 150104

150110\* packaging containing residues of or contaminated by hazardous substances

# **SECTION 14: Transport information**

14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

**IMDG** 

not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

NO DANGEROUS GOODS

ADR/RID

Inland navigation (ADN) NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 11 / 13

#### 14.3 Transport hazard class(es)

Transport by land according to ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

#### 14.4 Packing group

Transport by land according to ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

#### 14.5 Environmental hazards

Transport by land according to ADR/RID

nο

Inland navigation (ADN)

no

Marine transport in accordance with no

**IMDG** 

Air transport in accordance with IATA no

# 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

# 14.7 Maritime transport in bulk according to IMO instruments



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 12 / 13

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EEC-REGULATIONS** 2008/98/EG (2000/532/EC ); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707

- Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

- Annex I (REACH) The product is not subject to Annex I restrictions.

- Annex XIV (REACH) According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain

any substances ≥ 0.1% that are subject to authorisation.

- Annex XVII (REACH) According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains ≥ 0.1%

of substances with the following restrictions. 75

According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is subject to the

following restrictions.

3

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

NATIONAL REGULATIONS (UK): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH: GB CLP.

- Observe employment restrictions

for people

no

- VOC (2010/75/CE) 0%

#### 15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

#### 16.1 Hazard statements (SECTION 3)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H413 May cause long lasting harmful effects to aquatic life.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.03.2024, Revision 27.03.2024

Version 15.0. Supersedes version: 14.0

Page 13 / 13

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

# 16.3 Other information

Classification procedure Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position none